

**Panasonic**

Personal Facsimile

Model No. **KX-F590**

# OPERATING INSTRUCTIONS



Please read these Operating Instructions before using the unit.

**\* FAX PAPER \***

98 foot roll of Panasonic super thermal paper

— or —

164 foot roll of standard thermal paper  
(See page 61 for order numbers.)

Please read **IMPORTANT SAFETY INSTRUCTIONS** on page 60 before use. Read and understand all instructions.

**Caution:**

The Telephone Consumer Protection Act of 1991 makes it unlawful for any person to use a computer or other electronic device to send any message via a telephone facsimile machine unless such a message clearly contains in a margin on the top or bottom of at least the first sent page the following information:

- 1) Date and time of transmission; and,
- 2) Identification of either business, business entity or individual sending the message; and,
- 3) Telephone number of either the sending machine, business, business entity or individual.

In order to program this information into your facsimile machine, you must complete the steps on pages 30 to 31 in these Operating Instructions.

**Important Phone Numbers**

Authorized Service Center: 1-800-545-2672

Accessory Purchases: 1-800-332-5368

Technical Support: 1-800-HELP-FAX

**Accessories**

For recording paper replacement, see page 61.

Power  
cord ..... 1pc



(page 9)

Telephone line  
cord ..... 1pc




(page 9)

Paper  
stacker ... 1pc



(page 8)

Recording  
paper ..... 1pc



(page 8)

Handset .. 1pc



(page 9)

Handset  
cord ..... 1pc



(page 9)

Any details given in these instructions are subject to change without notice.  
The picture on the cover page may vary from the actual product.

**Thank you for purchasing the Panasonic Personal Facsimile.**

## **Features**

### **General**

- Desktop type
- LCD (Liquid Crystal Display) readout
- Automatic paper cutter
- Silent ring fax recognition system (page 23)
- Help function (see below)
- TAM (telephone answering machine) interface (page 18)
- Copier function (page 25)

### **Facsimile**

- Automatic document feeder (up to 15 sheets)
- 64-level halftones
- Resolution: standard/fine/super fine/half-tone (page 15)
- Delayed transmission (page 36)
- Ring pattern detection (page 41)
- Overseas transmission mode (page 44)
- Remote fax receiving using an extension phone (page 37)
- Junk mail prohibitor (page 39)
- Paper save function (page 45)

### **Integrated telephone system**

- One-touch dialer (10 phone numbers) (page 32)
- 22-station speed dialer (page 33)
- Hands-free speakerphone (page 12)
- Electronic telephone directory (page 34)

## **HELP function**



Use this function if the instructions are lost while using the unit. It will provide the user with instructions.

When the HELP button is pressed, the unit will print a quick reference.

### **Information:**

- When you use the unit with a telephone answering machine, transmit the leaflet on page 65 to several of your associates. In this way, you can confirm that your facsimile unit and telephone answering machine will function correctly and inform them of the procedure for transmitting documents and/or recording voice messages.

# Table of Contents

## 1 Installation and Preparation

|  |    |
|--|----|
| Location of Controls .....                 | 6  |
| Front view .....                           | 6  |
| Rear view .....                            | 6  |
| Control panel .....                        | 7  |
| Installing Your Unit .....                 | 8  |
| Installing the recording paper .....       | 8  |
| Installing the paper stacker .....         | 8  |
| Connections and dialing mode setting ..... | 9  |
| Adjusting Volumes .....                    | 10 |
| Selecting the Receive Mode .....           | 11 |

## 2 Basic Instructions

### Telephone

|  |    |
|--|----|
| Making and Answering Voice             |    |
| Calls .....                            | 12 |
| Making voice calls .....               | 12 |
| Making voice calls using automatic     |    |
| dialing .....                          | 12 |
| Redialing the last dialed number ..... | 13 |
| Voice muting .....                     | 13 |
| Answering voice calls .....            | 13 |
| Helpful hints for the speakerphone     |    |
| operation .....                        | 13 |

### Facsimile

|  |    |
|--|----|
| Before Transmission .....              | 14 |
| Acceptable documents .....             | 14 |
| Loading documents .....                | 15 |
| Setting resolution .....               | 15 |
| Sending 16 or more sheets .....        | 15 |
| Transmitting Documents .....           | 16 |
| Transmitting documents manually .....  | 16 |
| Transmitting documents with fewer      |    |
| procedures .....                       | 16 |
| Transmitting documents using automatic |    |
| dialing .....                          | 17 |
| Receiving Documents and/or             |    |
| Voice Calls .....                      | 18 |
| Manual reception .....                 | 18 |
| Automatic reception .....              | 18 |
| Receiving in the EXT. TAM mode .....   | 18 |
| Connection .....                       | 18 |

|  |    |
|--|----|
| How to receive incoming calls in the       |    |
| EXT. TAM mode .....                        | 19 |
| Setting up the answering machine .....     | 20 |
| Setting the remote TAM activation ID ..... | 20 |
| Setting the silent detection .....         | 21 |
| Notice when using with an                  |    |
| answering machine .....                    | 21 |
| Receiving in the TEL/FAX mode .....        | 22 |
| Setting the number of rings to answer      |    |
| in the TEL/FAX mode .....                  | 23 |
| Silent ring fax recognition system .....   | 23 |
| Receiving in the FAX mode .....            | 24 |
| Setting the number of rings in the         |    |
| FAX mode .....                             | 24 |

### Copier

|                     |    |
|---------------------|----|
| Making a Copy ..... | 25 |
|---------------------|----|

## 3 Basic Settings

|  |    |
|--|----|
| User Programmable Features .....               | 26 |
| Programming feature table .....                | 26 |
| How to enter letters and symbols .....         | 28 |
| To enter characters .....                      | 28 |
| Special uses of the direct call                |    |
| station keys .....                             | 29 |
| Setting the date and time .....                | 30 |
| Setting your logo .....                        | 30 |
| Setting your facsimile telephone               |    |
| number .....                                   | 31 |
| Setting the transmission report printing ..... | 31 |

|                                     |    |
|-------------------------------------|----|
| Storing Phone Numbers for Automatic |    |
| Dialing .....                       | 32 |
| Storing phone numbers for one-touch |    |
| dialing .....                       | 32 |
| Storing phone numbers for speed     |    |
| dialing .....                       | 33 |
| To keep a phone number secret ..... | 33 |

## 4 Advanced Instructions

|                                      |    |
|--------------------------------------|----|
| Electronic Telephone Directory ..... | 34 |
| How to use the electronic telephone  |    |
| directory .....                      | 34 |
| Polling .....                        | 35 |
| Polling reception .....              | 35 |
| Polling transmission (Polled) .....  | 35 |

|   |    |
|---|----|
| Delayed Transmission .....  | 36 |
| Remote Fax Receiving Using an<br>Extension Phone .....              | 37 |
| Using an extension phone .....                                      | 37 |
| Changing the remote fax activation<br>code .....                    | 38 |
| Junk Mail Prohibitor .....  | 39 |
| Setting the junk mail prohibitor .....                              | 39 |
| Transmitting documents to your unit<br>with the prohibitor ID ..... | 40 |
| Receiving with Distinctive Ring<br>Service .....                    | 41 |
| Programming the unit with distinctive<br>ringing pattern .....      | 42 |
| Special Settings .....  | 43 |
| Logo print position .....   | 43 |
| Overseas transmission mode .....                                    | 44 |
| Paper save reception/copy .....                                     | 45 |
| Extension copy .....  | 46 |
| Original mode .....   | 47 |
| Resetting the advanced features .....                               | 47 |
| Voice Contact .....   | 48 |
| Initiating voice contact .....                                      | 48 |
| Receiving a request for voice contact .....                         | 48 |
| TONE, FLASH and PAUSE   |    |
| Buttons .....   | 49 |
| TONE button .....   | 49 |
| FLASH button .....  | 49 |
| PAUSE button .....  | 49 |

## **5 Reports and Lists**

|                                     |    |
|-------------------------------------|----|
| Printing Reports and Lists .....    | 50 |
| How to print each report/list ..... | 50 |
| Sample reports and lists .....      | 51 |
| Setting journal auto print .....    | 53 |

## **6 Troubleshooting and Maintenance**

|  |    |
|--|----|
| Troubleshooting .....                                      | 54 |
| Error messages on the display .....                        | 54 |
| General corrective measures .....                          | 55 |
| Explanation of communication result<br>on the report ..... | 56 |
| Clearing a recording paper jam .....                       | 57 |
| Clearing a document jam .....                              | 58 |
| Adjusting the feeder pressure .....                        | 58 |
| Maintenance .....  | 59 |
| Cleaning the document feeder unit .....                    | 59 |
| Cleaning the thermal head .....                            | 59 |


## **7 General Information**

|                                     |    |
|-------------------------------------|----|
| Important Safety Instructions ..... | 60 |
| Accessory Order Information .....   | 61 |
| Specifications .....                | 61 |
| FCC Information .....               | 62 |
| Limited Warranty .....              | 63 |
| Index .....                         | 64 |
| FAX CORRESPONDENCE .....            | 65 |
| Speed dialer list .....             | 66 |
| Servicenter directory .....         | 67 |

## Location of Controls


### Front view

---




### Rear view

---



## Control panel




- ① **DIRECTORY button** (pages 12, 17 and 34)  
Used for speed dialing. Also used for the electronic telephone directory.
- ② **MENU button**  
Used to start and exit various programming.
- ③ **RECEIVE MODE button** (page 11)  
Used to select the desired receiving mode.
- ④ **RESOLUTION button** (page 15)  
Used to adjust scanning line density.
- ⑤ **Direct call station keys** (pages 12, 17 and 29)  
Used for one-touch dialing. Also used as character keys when logo and station names are programmed.
- ⑥ **HELP button** (page 3)  
Used to print an easy guide of operations.
- ⑦ **LOWER key** (pages 12, 17 and 32)  
Used to access lower stations (6 to 10) for one-touch dialing.
- ⑧ **TONE button** (page 49)  
Used to temporarily change the dialing mode from pulse to tone during a dialing operation.
- ⑨ **Dial keypad**  
Used for dialing operation and parameter setting. Also used as character keys.
- ⑩ **SP-PHONE/VOICE STDBY button** (pages 12 and 48)  
Used for on-hook dialing and voice contact features.
- ⑪ **MUTE button** (page 13)  
Used for voice muting.
- ⑫ **REDIAL/PAUSE button** (pages 13 and 49)  
Used to redial the last dialed number. Also used to insert a pause into a phone number.
- ⑬ **FLASH button** (page 49)  
Used as a hook button. Also used to access some features of your host exchange.
- ⑭ **STOP button** (page 16)  
Used to stop fax communication.
- ⑮ **COPY button** (page 25)  
Used to start copying.
- ⑯ **START/SET button**  
Used to start fax communication. Also used to store parameters during programming.
- ⑰ **VOLUME buttons** (page 10)  
Used to adjust the volume level of the ringer, speaker and handset.

## Installing Your Unit


### Installing the recording paper

---




1 Slide the lever toward you to open the top cover.

2 Place a recording paper roll in the unit.  
—Make sure that the shiny side of the paper is facing up and that there is no slack, tape or glue residue on the paper roll. (See note below.)



3 Insert the leading edge of recording paper under the green bar.

4 Close the top cover carefully by gently pressing down on both ends.




#### Notes:

- Use only the included roll or specified recording paper, or else the print quality may be affected and/or excessive thermal head wear may occur. See page 61 for order number.
- The start of some recording paper rolls is secured using glue or tape. Residue from this glue/tape may cause the paper cutter to jam immediately following installation of a new roll. To prevent this, cut approximately 150 mm (6 inches) from the new roll of paper prior to installation.

### Installing the paper stacker


---





## Connections and dialing mode setting

1



### Helpful hint for setting the dialing mode:


1. Ensure that the dialing mode selector is set to **TONE**.
2. Lift the handset or press the **SP-PHONE** button, then listen for the dial tone.
3. Dial a familiar number.
4. If the call is successful, the unit is connected to a tone exchange. Leave the selector set to **TONE**.
5. If the call is not successful, the unit is connected to a pulse exchange. Switch the selector to **PULSE**.

### Notes:

- We recommend the use of an exclusive power outlet to avoid interference from other equipment.
- When you operate this product, the socket outlet should be near the product and be easily accessible.
- The unit will not function during a power failure.
- You can connect an external telephone/answering machine to the unit after peeling off the tape on the external telephone jack (**EXT.**). When you use with an answering machine, see page 18.
- For additional equipment protection, we recommend the use of a surge protector. The following type is available; **TELESPIKE BLOK MODEL TSB** (TRIPPE MFG. CO.), **SPIKE BLOK MODEL SK6-0** (TRIPPE MFG. CO.), **SUPER MAX** (PANAMAX) or **MP1** (ITW LINX).

## Adjusting Volumes

You can adjust the volume level of the ringer, the handset and the speaker. These volume levels should be adjusted respectively.



**To increase the volume level:**

Press  $\wedge$  repeatedly.


**To decrease the volume level:**

Press  $\vee$  repeatedly.

—The number of the black squares in the display shows the volume level as below.

### Ringer volume

Press the buttons ( $\wedge/\vee$ ) repeatedly while the unit is in idle status. 3 levels are available.




**Note:**

- If the ringer volume is set to off, the unit will not ring and the display will show "RINGER OFF" in idle status.


### Handset volume

Press the buttons ( $\wedge/\vee$ ) repeatedly when the handset is in use. 3 levels are available.





### Speaker volume

Press the buttons ( $\wedge/\vee$ ) repeatedly when the speakerphone is in use. 8 levels are available.




## Selecting the Receive Mode

Select a desired receiving mode by pressing the **RECEIVE MODE** button repeatedly. The selected mode is displayed.




### **EXT. TAM mode:**

When you wish to connect a telephone answering machine (TAM) to record voice messages and also wish to receive fax messages, select this mode. For further details, see page 18.




### **TEL/FAX mode:**

When you wish to answer voice calls with ring and wish to receive fax messages without hearing ring, select this mode. You can answer voice calls only and will not be disturbed by incoming faxes. For further details, see page 22.



### **FAX mode:**

When you wish to receive fax transmissions only, select this mode. The unit will answer all calls and start to receive fax messages automatically. For further details, see page 24.



### **TEL mode:**


When you wish to set the unit not to answer any incoming calls automatically, select this mode. When you pick up the handset and fax reception is required, you can press the **START/SET** button to receive documents. If no one answers a call by 15 rings, the receiving mode will switch to the **TEL/FAX** mode automatically.

#### **Notes:**

- Regardless of above setting, you can make voice and fax calls.
- If an external telephone is connected, use **TEL/FAX**, **FAX** or **TEL** mode.

## Making and Answering Voice Calls

### Making voice calls



- ❶ Press **SP-PHONE** or lift the handset, then listen for the dial tone.
- ❷ Dial a phone number.
- ❸ When the other party answers, speak through the microphone or handset.
- ❹ When finished, press **SP-PHONE** again or place the handset on the cradle.


#### Helpful hints:

- If you wish to switch to the handset from the speakerphone, lift the handset. To switch to the speakerphone, press the **SP-PHONE** button.
- If you misdial, press the **FLASH** button firmly, then dial the correct number.
- Adjust the volume to a suitable level. See page 10.
- For helpful hints for the speakerphone operation, see page 13.

### Making voice calls using automatic dialing

You can dial a phone number automatically using one-touch dialing and speed dialing.

Before using automatic dialing, make sure that the desired telephone numbers have been stored in memory (see pages 32 and 33).




- ❶ Press **SP-PHONE** or lift the handset.
- ❷-a Using one-touch dialing:
  - When using the upper stations 1 to 5:  
Press the desired direct call station key.
  - When using the lower stations 6 to 10:  
Press **LOWER**, then press the desired direct call station key.
- ❷-b Using speed dialing:  
Press **DIRECTORY**, then press # and the desired 2-digit number (00–21).

#### Helpful hint:

- You can also use the electronic telephone directory to make a voice call (see page 34).

## Redialing the last dialed number

If the line is busy or you wish to redial the last dialed number, use the REDIAL/PAUSE button.



Press **SP-PHONE** or lift the handset, then press **REDIAL/PAUSE**.


**Note:**

- If the line is busy when using the speakerphone, the unit will automatically redial the number (see item 8 on page 61).

2

## Voice muting

The MUTE button will mute your voice during a telephone conversation. Using this feature, you can hear the voice of the other party, but the other party cannot hear your voice.



Press **MUTE** and confirm the MUTE indicator light is on.  
To resume the conversation, press **MUTE** again.

## Answering voice calls

When the unit rings, lift the handset or press **SP-PHONE** to answer the call.

When you have finished, replace the handset on the cradle or press **SP-PHONE**.

**Note:**

- For helpful hints for the speakerphone operation, see below.

## Helpful hints for the speakerphone operation

- Use the speakerphone in a quiet room for best performance.
- If the other party has difficulty hearing you, decrease the volume using the **VOLUME** buttons (see page 10).
- If you and the other party speak at the same time, parts of your conversation will be lost. To avoid this, speak alternately.


## Before Transmission

### Acceptable documents


The unit can transmit documents that meet the following conditions.

- Document width should be from 128 to 216 mm (5 to 8½").
- Maximum document length should not exceed 600 mm (23⅝").
- Effective scanning width can be up to 208 mm (8⅜").
- Number of pages that can be set in the document feeder tray must not exceed 15 sheets.
- Document weight:
  - Single sheet: 45 to 90 g/m<sup>2</sup> (12 to 24 lb.)
  - Multiple sheets: 60 to 75 g/m<sup>2</sup> (16 to 20 lb.)


**Minimum document size**



**Maximum document size**




**Effective scanning width**



**Note:**

- Do not feed the following types of documents. Make a copy of these documents with a copier machine and feed the copy into the unit.
  - Paper with a chemically treated surface such as carbon paper or carbonless duplicating paper
  - Electrostatically charged paper
  - Heavily curled, creased or torn paper
  - Paper with a coated surface
  - Small-sized paper such as a slip or voucher
  - Thin paper less than 45 g/m<sup>2</sup> (12 lb.)
  - Thick paper over 90 g/m<sup>2</sup> (24 lb.)
  - Paper with faint contrast between the printing and the background
  - Paper with printing on the reverse side that can be seen through the front (e.g. newspaper)

## Loading documents



- ❶ Open the document feeder tray.
- ❷ Insert the documents **FACE DOWN** until a beep tone is heard.  
—The unit can accept up to 15 sheets of paper at a time.
- ❸ Adjust the document guides to the width of the documents.
- ❹ Adjust the resolution by pressing **RESOLUTION** if needed (see below).

### Notes:

- Remove clips, staples or other similar objects from a document before feeding it into the unit. Also check that all ink, paste or correction fluid on the document has completely dried.
- If the top edge of the document is curled, make it flat and insert the document.

## Setting resolution

Depending on the quality of the originals, you can select the desired resolution by pressing the **RESOLUTION** button repeatedly. Use the button when the document has been fed into the unit.

|            |   |
|------------|---|
| STANDARD   | Suitable for printed or typewritten originals with normal-sized characters. |
| FINE       | Suitable for originals with small printing.                                 |
| SUPER FINE | Suitable for originals with minute printing.                                |
| HALF TONE  | Useful for originals containing photographs, shaded drawings, etc.          |

### Notes:


- Using these features except the standard resolution will increase the transmission time.
- The super fine resolution only works between other compatible machines.
- If the setting is changed during feeding, it will be effective from the next sheet.
- To enhance the resolution settings, see page 47.

## Sending 16 or more sheets

If you wish to send 16 or more sheets at a time, insert the first 15 sheets of the document. Then add the extra sheets, up to 15 sheets at a time, before the last sheet is fed into the unit.

## Transmitting Documents

### Transmitting documents manually




- ❶ Insert the documents **FACE DOWN** until a beep tone is heard.
- ❷ Press **SP-PHONE** or lift the handset, then listen for the dial tone.
- ❸ Dial a phone number.
- ❹ When a fax tone is heard, press **START/SET**.
- ❺ Place the handset on the cradle if using it.  
—The unit will start transmission.

#### Notes:

- If the other party answers your call, ask them to press their start or transmit button to start the fax reception, then press your **START/SET** button.
- If there is a misdial in step 3, press the **FLASH** button firmly, then dial the correct number after the dial tone is heard.
- To interrupt the transmission, press the **STOP** button.

### Transmitting documents with fewer procedures

You can transmit documents without using the handset or the SP-PHONE button.



- ❶ Insert the documents **FACE DOWN** until a beep tone is heard.
- ❷ Enter the phone number.  
—If incorrect, press the **STOP** button, then enter the correct number.
- ❸ Press **START/SET**.  
—The unit will start to dial and transmit the documents.

#### Note:

- If there is no answer or the line is busy, the unit will automatically redial the number (see item 7 on page 61).




## Transmitting documents using automatic dialing

You can transmit documents automatically using one-touch dialing and speed dialing.

Before using automatic dialing, make sure that the desired telephone numbers have been stored in memory (see pages 32 to 33).

### Using one-touch dialing:



❶ Insert the documents **FACE DOWN** until a beep tone is heard.

❷ **When using the upper stations 1 to 5:**  
Press the desired direct call station key.


**When using the lower stations 6 to 10:**  
Press **LOWER**, then press the desired direct call station key.

—The unit will dial and transmit the documents automatically.

**Note:**

- If there is no answer or the line is busy, the unit will automatically redial the number (see item 7 on page 61).

### Using speed dialing:



❶ Insert the documents **FACE DOWN** until a beep tone is heard.

❷ Press **DIRECTORY**.

❸ Press **#**, then press the desired 2-digit number (00–21).  
—The unit will dial and transmit the documents automatically.


**Note:**

- If there is no answer or the line is busy, the unit will automatically redial the number (see item 7 on page 61).

## Receiving Documents and/or Voice Calls

### Manual reception

When in the *TEL* mode or during a telephone conversation, you can receive documents as follows.



- ❶ When the unit rings, press **SP-PHONE** or lift the handset to answer the call.
- ❷ When document reception is required, or a slow beep or nothing is heard, press **START/SET**.
- ❸ Place the handset on the cradle if using it.  
—The unit will start reception.

**Note:**

- To interrupt reception, press the **STOP** button.  
The unit will stop receiving.

### Automatic reception

Set the receive mode to *EXT.*, *TAM*, *TEL/FAX* or *FAX* by pressing **RECEIVE MODE**.


When a fax call comes in, the unit will automatically activate the fax function to receive documents.

### Receiving in the *EXT.* *TAM* mode

This mode is used only when an external telephone answering machine (TAM) has been connected to the facsimile unit. Incoming voice messages will be recorded on the telephone answering machine and fax calls will be received by the facsimile unit automatically.


### Connection

Connect the telephone answering machine to the jack marked "EXT.".



## How to receive incoming calls in the EXT. TAM mode

When a call comes in, the facsimile unit and the external telephone answering machine will work as follows.



### Helpful hint:

- When you use the unit with a telephone answering machine, transmit the leaflet on page 65 to several of your associates. In this way, you can confirm that your facsimile unit and telephone answering machine will function correctly and inform them of the procedure for transmitting documents and/or recording voice messages.

## Setting up the answering machine









1. Set the number of rings on the telephone answering machine to 1–4
2. Record your greeting message referring to the example below.  
 “This is (your name, business and/or telephone number). We are unable to answer right now. To leave a message, speak after the long beep. To send a fax, press your asterisk button twice (remote fax activation code) and start transmission. Thank you.”  
 —Do not pause more than 4 seconds in the message.  
 —Record your message for 8–16 seconds. We recommend you keep it around 10 seconds in length.
3. If your external telephone answering machine is equipped with a remote operation feature, you must set the same remote access code (remote TAM activation ID) as stored on the telephone answering machine in the unit's memory. See below.

## Setting the remote TAM activation ID

Your code can be from 1 to 5 digits long. The numbers 0 through 9 and characters # and \* may be used.

### Important:

- Note that the code should be different from the remote fax activation code (see page 38) and the junk mail prohibitor ID (see page 39).







|  |  |   |  |
|--|--|---|--|
| <b>1</b>    | Press <b>MENU</b> .<br><div>1.SYSTEM SET UP</div>                  | <b>5</b>    | Press <b>START/SET</b> .<br><div>ID=11</div> |
| <b>2</b>  | Press #, then press 11.<br><div>REMOTE TAM ACT.</div>              | <b>6</b>  | Enter the new ID number.                     |
| <b>3</b>  | Press <b>START/SET</b> .<br><div>MODE=OFF [▲▼]</div>               | <b>7</b>  | Press <b>START/SET</b> to store the number.  |
| <b>4</b>  | Press ▲ or ▼ repeatedly to select “ON”.<br><div>MODE=ON [▲▼]</div> | <b>8</b>  | Press <b>MENU</b> to end the program.        |

## Setting the silent detection

This feature allows the facsimile unit to activate the fax function automatically when a silent pause longer than 4 seconds is detected in the *EXT. TAM* mode.

### Helpful hints:

- If you wish to receive documents from stations that do not send calling tone (CNG) after dialing, set this feature to "ON".
- If you use a single cassette tape to give a greeting message and to record incoming messages, set this feature to "OFF".


|   |   |  |  |
|---|---|--|--|
| <b>1</b>   | Press <b>MENU</b> .<br><div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">1.SYSTEM SET UP</div>   | <b>4</b>   | Press <b>▲</b> or <b>▼</b> to select the desired mode. |
| <b>2</b>   | Press <b>#40</b> .<br><div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">SILENT DETECT.</div>     | <b>5</b>   | Press <b>START/SET</b> to store the setting.           |
| <b>3</b>  | Press <b>START/SET</b> .<br><div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">MODE=ON {▲▼}</div> | <b>6</b>  | Press <b>MENU</b> to end the program.                  |

## Notice when using with an answering machine

- Every time the facsimile unit receives a document, a mute or a fax tone may be recorded on the tape.
  - Advise callers that they should not pause for over 4 seconds while recording their messages. If they do, the facsimile unit may activate the fax function.
  - When your answering machine runs out of a recording tape, your facsimile unit may not be able to receive a document. Rewind the tape and prepare for recording.
  - When you set the answering machine to give only a greeting message, a fax reception may not be available. We recommend to set your answering machine to record messages.
  - If you answer a call with the answering machine and pause for over 4 seconds, the facsimile unit may activate the fax function and you may not be able to talk with the other party. To resume the conversation, press the **STOP** button on the facsimile unit.
  - When the answering machine does not answer a call after ringing 5 times, the facsimile unit will activate the fax function.
  - Set the receive mode of the facsimile unit to **TEL** in the following conditions:
    - when you wish to set the number of rings on the answering machine to more than 5.
    - when you wish to use auto transfer functions (transfer, pager call, etc.) on the answering machine.
- Note that automatic fax sending (see page 19) can not be received automatically in the **TEL** mode.

## Receiving in the TEL/FAX mode

When a call comes in, the unit will work as follows.












### Notes:

- The unit can distinguish between a voice and fax call by detecting the calling tone (CNG), sent by the transmitting fax machines.  
Some fax messages that are transmitted manually may not send with a calling tone. These calls must be manually received after the unit rings and the call is answered.
- If a voice call is received, the unit will start to ring. While ringing, the unit will emit a different ring back tone to the calling party.
- If you hear the facsimile unit ringing, you can pick up the handset on the facsimile unit or another extension (if connected on the same line) to answer the call.

## Setting the number of rings to answer in the TEL/FAX mode

This feature determines the number of rings after which the unit answers a call in the *TEL/FAX* mode. You can change the number of rings among 1 to 4 rings.










- 1**  Press **MENU**.  

- 2**  Press **#06**.  

- 3**  Press **START/SET**.  

- 4**  Press **▲** or **▼** to select the desired number of rings (1 to 4).
- 5**  Press **START/SET** to store the setting.
- 6**  Press **MENU** to end the program.

### Note:

- If an external telephone with a caller ID feature is connected, set the number of rings to more than 2.

## Silent ring fax recognition system

In the *TEL/FAX* mode, when a fax call is received, the unit will automatically activate the fax function without ringing (we call this "silent ring fax recognition system"). If the unit detects a voice call, it will ring 3 times. This number of rings can be changed to a maximum of 6 by following steps below.

- 1**  Press **MENU**.  

- 2**  Press **#30**.  

- 3**  Press **START/SET**.  

- 4**  Press **▲** or **▼** to select the desired number of rings (3 to 6).
- 5**  Press **START/SET** to store the setting.
- 6**  Press **MENU** to end the program.

## Receiving in the FAX mode







When a call comes in, the unit will automatically answer the line after 1 to 4 rings (user programming) and activate the fax function.

### Setting the number of rings in the FAX mode

This feature determines the number of rings after which the unit answers a call in the FAX mode. You can change the number of rings from 1 to 4 rings.

#### Helpful hints:


- If you wish to have the opportunity to answer a call before the unit does, increase the number of rings.
- If you find there is difficulty in fax receiving from machines that have an automatic transmission feature, decrease the number of rings.
- If an external telephone with a caller ID feature is connected, set the number of rings to more than 2.

|  |  |   |  |
|--|--|---|--|
| <b>1</b>    | Press <b>MENU</b> .<br><div style="border: 1px solid black; padding: 2px; display: inline-block;">1.SYSTEM SET UP</div>  | <b>4</b>    | Press <b>▲</b> or <b>▼</b> to select the desired number of rings (1 to 4). |
| <b>2</b>   | Press <b>#07</b> .<br><div style="border: 1px solid black; padding: 2px; display: inline-block;">FAX RING</div>          | <b>5</b>   | Press <b>START/SET</b> to store the setting.                               |
| <b>3</b>  | Press <b>START/SET</b> .<br><div style="border: 1px solid black; padding: 2px; display: inline-block;">RING=1 [▲▼]</div> | <b>6</b>  | Press <b>MENU</b> to end the program.                                      |



## Making a Copy

Any transmissible document can be copied (see page 14). To make a copy, follow the steps below.



**1** Insert the documents **FACE DOWN**.

**2** Press **COPY**.  
—The unit will start copying.

**Notes:**

- When copying, the unit will automatically select the *FINE* resolution. Depending on the originals, select the desired resolution (see page 15).
- You can make or receive voice calls while making a copy.
- To interrupt a copy, press the **STOP** button. The unit will stop copy operation and eject the documents.

## User Programmable Features

The unit has the following programming features.

**Basic features** are the settings that need to be programmed upon completing the installation. Most probable choices have been pre-selected, but some features, such as codes #01, #02 and #03, must be programmed by user.

**Advanced features** should be programmed as the need arises.

### Programming feature table

#### Basic features

| Code | Feature                   | Description   | Selection  | Page |
|------|---------------------------|---|--|------|
| #01  | SET DATE & TIME           | Setting the current date and time.  |  | 30   |
| #02  | YOUR LOGO                 | Setting your company name or personal name.   | up to 30 digits                                      | 30   |
| #03  | YOUR TELEPHONE NUMBER     | Setting your facsimile telephone number.  | up to 20 digits                                      | 31   |
| #04  | PRINT TRANSMISSION REPORT | Setting individual transmission report printing.  | <u>ERROR</u> /ON/OFF                                 | 31   |
| #06  | TEL/FAX DELAYED RING      | Setting the number of rings on the extension phone (if connected) before the facsimile unit answers a call in the TEL/FAX mode. | <u>1</u> to 4 rings                                  | 23   |
| #07  | FAX RING COUNT            | Setting the number of rings to answer in the FAX mode.  | <u>1</u> to 4 rings                                  | 24   |
| #11  | REMOTE TAM ACTIVATION     | Setting the same remote control code as stored on the telephone answering machine.  | ON/ <u>OFF</u><br>ID=up to 5 digits<br>( <u>11</u> ) | 20   |

**Note:** In the "Selection" column, the underlined print indicates the pre-selected settings.

**Advanced features**

| Code | Feature                     | Description  | Selection  | Page |
|------|-----------------------------|--|--|------|
| #21  | LOGO POSITION               | Setting the logo print position on the transmitted document.   | <u>OUT</u> /IN/OFF   | 43   |
| #22  | JOURNAL AUTO PRINT          | Printing journal report automatically.   | <u>ON</u> /OFF   | 53   |
| #23  | OVERSEAS MODE               | Setting the overseas transmission mode.  | ON/ <u>OFF</u>   | 44   |
| #24  | JUNK MAIL PROHIBITOR        | Turning on the junk mail prohibitor feature. Also setting the prohibitor ID.   | ON/ <u>OFF</u><br>Prohibitor ID=<br>2 digits ( <u>22</u> ) | 39   |
| #25  | DELAYED TRANSMISSION        | Setting the delayed transmission.  | ON/ <u>OFF</u>   | 36   |
| #30  | SILENT FAX RECOGNITION RING | Setting the number of rings when receiving a voice call in the TEL/FAX mode.   | <u>3</u> to 6 rings  | 23   |
| #31  | RING DETECTION              | Setting the distinctive ring pattern that will be detected.  | A/B/C/D/ <u>OFF</u>  | 42   |
| #33  | PAPER SAVE FUNCTION         | Setting the paper save reception/copy.   | ON/ <u>OFF</u>   | 45   |
| #34  | EXTENSION COPY              | Copying a document twice in length.  |  | 46   |
| #40  | SILENT DETECTION            | Selecting whether or not the unit will activate fax function when a silent pause longer than 4 seconds occurs in the EXT. TAM mode after the call is answered. | <u>ON</u> /OFF   | 21   |
| #41  | REMOTE FAX ACTIVATION CODE  | Setting the remote fax activation code for remote receiving using an extension phone.  | up to 4 digits<br>( <u>**</u> )                            | 38   |
| #46  | ORIGINAL SETTING            | Setting the contrast mode.   | <u>NORMAL</u> /<br>LIGHT/<br>DARKER                        | 47   |
| #80  | SET DEFAULT                 | Resetting the parameters of the advanced features.   | YES/ <u>NO</u>   | 47   |

**Note:** In the "Selection" column, the underlined print indicates the pre-selected settings.


## How to enter letters and symbols

The dial keypad and the direct call station 1 are used as alphabet and symbol character input keys when you enter your logo and station names for automatic dialers.

### To enter characters

Pressing each key will alternately select a character as shown below.

When the desired character is displayed, press # to move the cursor to the right and enter the next character.

| Keys  | Number of pressing times                     |   |   |   |   |   |   |   |    |    |    |    |    |
|---|--|---|---|---|---|---|---|---|----|----|----|----|----|
|   | 1  | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9  | 10 | 11 | 12 | 13 |
| (1)   | 1  | [ | ] | { | } | + | - | / | =  | ,  | .  | _  | '  |
| (2)   | A  | B | C | a | b | c | 2 | . |    |    |    |    |    |
| (3)   | D  | E | F | d | e | f | 3 |   |    |    |    |    |    |
| (4)   | G  | H | I | g | h | i | 4 |   |    |    |    |    |    |
| (5)   | J  | K | L | j | k | l | 5 |   |    |    |    |    |    |
| (6)   | M  | N | O | m | n | o | 6 |   |    |    |    |    |    |
| (7)   | P  | Q | R | S | p | q | r | s | 7  |    |    |    |    |
| (8)   | T  | U | V | t | u | v | 8 |   |    |    |    |    |    |
| (9)   | W  | X | Y | Z | w | x | y | z | 9  |    |    |    |    |
| (0)   | 0  | ( | ) | < | > | ! | " | # | \$ | %  | &  | ¥  |    |
| 0  | :  | ; | ? | ! | * | @ | ^ | ' | →  |    |    |    |    |
| (*)   | ◀ key (Used to move the cursor to the left)  |   |   |   |   |   |   |   |    |    |    |    |    |
| (□)   | ▶ key (Used to move the cursor to the right) |   |   |   |   |   |   |   |    |    |    |    |    |

For example, when entering "Mike" as your logo:

- ① Press 6 once, then press #.

LOGO=M□

- ② Press 4 six times, then press #.

LOGO=Mi□

- ③ Press 5 five times, then press #.

LOGO=Mik□

- ④ Press 3 five times.


LOGO=Mike

#### Note:

- If you make a mistake while programming, use # or \* to move the cursor to the incorrect character, then make the correction.


## Special uses of the direct call station keys

Direct call stations 2, 4 and 5 are used as command keys.



The layout of the direct call station keys is printed on the reverse side of the directory card.

1. Remove the directory card cover with a pencil or similar object as shown.
2. Turn over the directory card. You will find how each command is assigned to the direct call station keys.



### ■ Direct call station 2 (INSERT):

This key is used to insert one character (or one space) in the programmed logo.

Example: Compny→Company

1. Press # or \* repeatedly until the cursor is positioned on "n".

LOGO=Compny

2. Press **INSERT**.

LOGO=Comp ny

3. Press **2** repeatedly until "a" is shown.

LOGO=Company

### ■ Direct call station 4 (SPACE):

This key is used to replace one character with a space.

### ■ Direct call station 5 (DELETE):

This key is used to delete one character from the programmed logo.

Example: Comnpany→Company

1. Press # or \* repeatedly until the cursor is positioned on "n".







LOGO=Comnpany

2. Press **DELETE**.

LOGO=Company

## Setting the date and time

The internal clock of the unit will print the date and time, on the top line of all fax messages you transmit, and on the fax communication reports such as the journal report and the transmission report.







|   |  |   |  |
|---|--|---|--|
| <p><b>1</b></p>  | <p>Press <b>MENU</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">1.SYSTEM SET UP</div>      | <p><b>4</b></p>   | <p>Enter the current month/day/year/hour/minute by selecting each 2 digits. Then press * for AM or press # for PM.</p> |
| <p><b>2</b></p>  | <p>Press <b>#01</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">SET DATE &amp; TIME</div>   | <p><b>Example: Aug. 10 1995, 3:00 PM</b><br/>Press 08 10 95 03 00, then press # to select PM.</p>   |  |
| <p><b>3</b></p>  | <p>Press <b>START/SET</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">01/01/94 12:00A</div> |   |  |
|   |  | <p><b>5</b></p>   | <p>Press <b>START/SET</b> to store the setting.</p>  |
|   |  | <p><b>6</b></p>  | <p>Press <b>MENU</b> to end the program.</p>   |

### Notes:

- When you make a mistake while programming, press the **STOP** button, then make the correction.
- The accuracy of the clock will be approximately  $\pm 45$  seconds a month at room temperature.

## Setting your logo

The logo is used to identify fax messages that are being transmitted by your unit. It may consist of alpha-numeric letters and symbols. Usually the logo is a company, division or personal name in an abbreviated form.


|   |   |  |  |
|---|---|--|--|
| <p><b>1</b></p>  | <p>Press <b>MENU</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">1.SYSTEM SET UP</div> | <p><b>4</b></p>  | <p>Enter your logo up to 30 characters by following the instructions on page 28.</p> |
| <p><b>2</b></p>  | <p>Press <b>#02</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">YOUR LOGO</div>        | <p><b>5</b></p>  |  |
| <p><b>3</b></p>  | <p>Press <b>START/SET</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content;">LOGO=</div>      |  |  |
|   |   | <p><b>6</b></p>  | <p>Press <b>MENU</b> to end the program.</p>   |



### Note:



- When the first character is entered, the preset logo will be cleared.





## Setting your facsimile telephone number

Your programmed phone number will be printed on the top of each page transmitted from your unit.

- 1**  Press **MENU**.


- 2**  Press **#03**.


- 3**  Press **START/SET**.


- 4**  Enter your facsimile telephone number up to 20 digits.  
—The # button provides a space and the \* button provides "+".
- 5**  Press **START/SET** to store the setting.
- 6**  Press **MENU** to end the program.

## Setting the transmission report printing

Each time a document is transmitted, this feature will give you a printed record of the transmission.

The following choices are available:


**ERROR:** The report will print only when the transmission fails.



**ON:** The report will print, indicating whether the transmission is successful or not.



**OFF:** The report will not print.





**Sample of transmission report:**

| XMT REPORT           |                 |                 |            |      |       |        |
|----------------------|-----------------|-----------------|------------|------|-------|--------|
| Jan. 01 1994 12:09AM |                 |                 |            |      |       |        |
| NO.                  | OTHER FACSIMILE | START TIME      | USAGE TIME | MODE | PAGES | RESULT |
| 01                   | COMPANY ABC     | Jan. 01 12:00AM | 01'05      | TX   | 01    | OK     |

- 1**  Press **MENU**.


- 2**  Press **#04**.


- 3**  Press **START/SET**.


- 4**  Press **▲** or **▼** to select the desired mode.
- 5**  Press **START/SET** to store the setting.
- 6**  Press **MENU** to end the program.

## Storing Phone Numbers for Automatic Dialing


The unit's memory allows you to use both one-touch dialing (up to 10 phone numbers) and speed dialing (up to 22 phone numbers) for rapid access to your most frequently dialed numbers.

**One-touch dialing:** The unit is equipped with 5 direct call station keys, each of which is divided into an upper station and a lower station.

**Speed dialing:** The unit is equipped with additional 22 dialing stations. These stations are assigned to 2-digit numbers (00–21).


### Storing phone numbers for one-touch dialing

Each station can store a phone number up to 30 digits in length and the associated station name up to 10 alpha-numeric characters.

**1** 

Press **MENU** repeatedly until the following is displayed.

2. STORE TEL NO.

**2** 

**For upper stations 1 to 5:**  
Press one of the direct call station keys.  
*Example: Station 4*


<S04>=

or


**For lower stations 6 to 10:**  
Press **LOWER**, then press one of the direct call station keys.  
*Example: Station 8*

<LWR>=

<S08>=


**3** 

Enter a phone number.


**4** 

Press **START/SET** to store the number.


NAME=

**5** 

Enter the station name by following the instructions on page 28.

**6** 

Press **START/SET** to store the station name.  
—To program other stations, repeat from step 2.

**7** 

Press **STOP** to end the program.


#### Notes:


- To enter a hyphen in a phone number, press the **LOWER** key.
- If you make a mistake while programming, press the **STOP** button, then make the correction.
- To erase a programmed phone number in step 3, press the **STOP** button when the cursor is positioned on the beginning of the number.
- Confirm that phone numbers and their station names have been correctly stored by printing the telephone number list (see page 50).








## Storing phone numbers for speed dialing

Each dialing station can store a phone number up to 30 digits in length and the associated station name up to 10 alpha-numeric characters.

- 1**  Press **MENU** repeatedly until the following is displayed.

2. STORE TEL NO.
- 2**  Press #, then press a 2-digit number (00–21).  
**Example:** Station #00

<A00>=
- 3**  Enter a phone number.
- 4**  Press **START/SET** to store the number.


NAME=
- 5**  Enter the station name by following the instructions on page 28.
- 6**  Press **START/SET** to store the station name.  
—To program other stations, repeat from step 2.
- 7**  Press **STOP** to end the program.

### Notes:

- To enter a hyphen in a phone number, press the **LOWER** key.
- If you make a mistake while programming, press the **STOP** button, then make the correction.
- To erase a programmed phone number in step 3, press the **STOP** button when the cursor is positioned on the beginning of the number.
- Confirm that phone numbers and their station names have been correctly stored by printing the telephone number list (see page 50).

## To keep a phone number secret

Use this feature to keep a whole phone number or a portion of a phone number secret. When the telephone number list is printed out (see pages 50 and 51), secret numbers will not be printed.



### Using the **SECRET** (direct call station 3) button:

Press the **SECRET** button before and behind the phone number you wish to keep secret.

**Example:** The phone number you wish to keep secret is 12345.  
Press **SECRET**, 12345 and **SECRET** again.

<A01>= [12345]

### Note:

- Pressing the **SECRET** button once counts as two digits.


## Electronic Telephone Directory

The station names stored in memory for automatic dialing are automatically registered in the electronic telephone directory in alphabetical order.

With the electronic telephone directory feature, you can make a fax or voice call by selecting the desired station name on the display.

### How to use the electronic telephone directory

To search a station name and make a voice or fax call, proceed as follows.  
If you wish to send a fax, insert the documents into the document feeder first.



- ① Press **DIRECTORY**.

SELECT INDEX

- ② ■ Press a dial key to which the initial of a station name is assigned (see Index table).

**Example:** To search a name with the initial "N"

Press **6** repeatedly until the first station name with the initial "N" is displayed and press **▼** until the desired name is displayed.

or

- Press **▲** or **▼** repeatedly until the desired name is displayed.

- ③ Press **START/SET**.

—The unit will start dialing.

—If a document has been fed into the unit, the transmission will start.

Index table


| Dial key | Index      | Dial key | Index  |
|----------|------------|----------|--|
| 1        | 1          | 7        | P, Q, R, S, 7                                    |
| 2        | A, B, C, 2 | 8        | T, U, V, 8                                       |
| 3        | D, E, F, 3 | 9        | W, X, Y, Z, 9                                    |
| 4        | G, H, I, 4 | 0        | 0  |
| 5        | J, K, L, 5 | *        | Other symbols                                    |
| 6        | M, N, O, 6 | #        | (Used for speed dialing.<br>See pages 12 and 17) |


## Polling



Polling means that you call another facsimile machine to retrieve a document. On the other hand, the documents loaded on your unit can be retrieved only at the request of the calling machines (we call this "Polled" mode).

### Polling reception

Make sure that no documents have been fed into your unit and that the other party's machine is ready for your call.

- 1  Press **MENU** repeatedly until the following is displayed.  

4 . POLLING
- 2  Press **START/SET**.  




NO. =
- 3  Enter the phone number by using one-touch dialing, speed dialing or a full number.
- 4  Press **START/SET**.  
—The unit will start polling.


#### Notes:


- The receiving unit incurs any telephone charges.
- If there is no answer or the line is busy, the unit will automatically redial the number (see item 7 on page 61).

### Polling transmission (Polled)


To let other machines retrieve documents loaded on your unit, proceed as follows.

- 1  Set the unit in the **EXT. TAM, TEL/FAX** or **FAX** mode by pressing **RECEIVE MODE**.
- 2  Insert the documents **FACE DOWN**.
- 3  Press **MENU** repeatedly until the following is displayed.  

5 . POLLED
- 4  Press **START/SET**.  

MODE=OFF [▲▼]
- 5  Press **▲** or **▼** to select "ON".  

MODE=ON [▲▼]

  
—If this feature is not required, select "OFF".
- 6  Press **START/SET**.  


















POLLED ON

#### Note:

- When delayed transmission (see page 36) is set to **ON**, this feature is not available.

## Delayed Transmission

Using a built-in clock, the unit can send documents automatically at a specific time. This allows you to take advantage of low-cost calling hours given by some telephone companies. The delayed transmission can be reserved to take place up to 24 hours.

- 1**  Insert the documents **FACE DOWN**.
- 2**  Press **MENU**.  

- 3**  Press **#25**.  

- 4**  Press **START/SET**.  

- 5**  Press **▲** or **▼** to select "ON".  
  
 —If this feature is not required, select "OFF".
- 6**  Press **START/SET**.  

- 7**  Enter the phone number using one-touch dialing, speed dialing or a full number.  
 —You can use the electronic telephone directory (see page 34).
- 8**  Press **START/SET** to store the number.  

- 9**  Enter the transmission start time.  
**Example: 11:00PM**  
 Press **1100**, then press **#** to select PM.  
 —To select AM, press **\***.
- 10**  Press **START/SET** to store the setting.
- 11**  Press **MENU** to end the program.  
 —When the programmed time has come, the unit will automatically start transmission.

### Notes:

- If there is no answer or the line is busy, the unit will automatically redial the number (see item 7 on page 61).
- You can receive, transmit and copy documents while the delayed transmission is set. To copy or transmit documents, remove documents from the tray and replace them when you have finished.
- If the programmed start time has passed during a power failure, delayed transmission will be attempted soon after the power is restored.
- When polling transmission feature (see page 35) is set to ON, this feature is not available.

## Remote Fax Receiving Using an Extension Phone


If you have an extension phone connected to the facsimile unit or connected on the same line, it is possible to receive a fax message into your facsimile unit by using the touch tone extension phone. This saves you the trouble of going to the facsimile unit and pressing the START button.

**Important:**

- This feature is available when you receive a call.
- To activate this feature, use a touch tone telephone as an extension phone and dial the remote fax activation code. The remote fax activation code is set to “\*\*” as a preselected setting.

### Using an extension phone

---



- ① When a call comes in, lift the handset of the extension phone.
- ② If a slow beep is heard, or the other party wishes to send you a fax, press the remote fax activation code.
- ③ Replace the handset on the cradle.  
—The facsimile unit will activate the fax function to receive documents.

**Note:**


- The remote fax activation code can be changed. See page 38.

## Changing the remote fax activation code


Your code can be from 1 to 4 digits long. The numbers 0 through 9 and character \* may be used. (e.g. \*\*, 234, 234\*)

### Important:


- The remote fax activation code should be different from the remote TAM activation ID (see page 20).

- 


Press **MENU**.


1.SYSTEM SET UP
- 


Press **#41**.

REMOTE FAX ACT.
- 

Press **START/SET**.

CODE=\*\*
- 

Enter the new code number.
- 

Press **START/SET** to store the number.
- 

Press **MENU** to end the program.

### Note:

- If the remote fax activation code is set to "0000", the unit does not work properly.

## Junk Mail Prohibitor

The feature is effective to prevent fax receptions from unauthorized stations.









With this feature, the unit can receive documents only from the stations whose phone numbers are stored for automatic dialing.

If you wish to receive documents from other stations, advise the caller to call your unit manually and enter your prohibitor ID (see page 40) before initiating transmission.

### Important:

- To activate this feature, set the unit in the EXT. TAM, TEL/FAX or FAX mode and let the unit receive documents automatically.
- When in the EXT. TAM or TEL/FAX mode, transmission using the prohibitor ID is available (see page 40).
- If manual reception is used, the documents from any transmitting stations will be received.
- If the transmitting machines have not been programmed with their facsimile telephone numbers, the unit will not be able to receive documents automatically.

## Setting the junk mail prohibitor

|   |   |  |   |
|---|---|--|---|
| <p><b>1</b></p>    | <p>Press <b>MENU</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 5px auto;">1.SYSTEM SET UP</div>   | <p><b>5</b></p>    | <p>Press <b>START/SET</b> to store the setting.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 5px auto;">ID=22</div> |
| <p><b>2</b></p>  | <p>Press <b>#24</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 5px auto;">JUNK MAIL PROH.</div>  | <p><b>6</b></p>  | <p>If you wish to change the junk mail prohibitor ID, enter the desired 2-digit number.<br/>—0, # and * cannot be used.</p>                               |
| <p><b>3</b></p>  | <p>Press <b>START/SET</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 5px auto;">MODE=OFF [▲▼]</div>  | <p><b>7</b></p>  | <p>Press <b>START/SET</b> to store the number.</p>  |
| <p><b>4</b></p>  | <p>Press <b>▲</b> or <b>▼</b> to select "ON".</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 5px auto;">MODE=ON [▲▼]</div> <p>—If this feature is not required, select "OFF".</p> | <p><b>8</b></p>  | <p>Press <b>MENU</b> to end the program.</p>  |

### Note:

- The junk mail prohibitor ID must be different from the first 2 digits of the remote TAM activation ID (see page 20). For example, if the remote TAM activation ID is set to "321", do not use "32" as a junk mail prohibitor ID.

## Transmitting documents to your unit with the prohibitor ID \_\_\_\_\_


If the junk mail prohibitor feature is activated, automatic fax reception from unauthorized stations will not be available. However, in this instance, a caller can transmit documents to your unit manually by entering the prohibitor ID.

Issue the prohibitor ID to callers with priority status.

### Important:

- Transmission with the prohibitor ID is activated when your unit is in the **EXT. TAM** or **TEL/FAX** mode.

### Instructions for caller:



- 1 A caller may call your unit.
- 2 ■ **When your unit is in the *EXT. TAM* mode:**  
They may enter the prohibitor ID while the greeting message is being played or during an incoming message recording mode.  
  
or  
  
■ **When your unit is in the *TEL/FAX* mode:**  
They may enter the prohibitor ID while the different ring back tone is heard.
- 3 When a fax tone is heard, they may press their start or transmit button to start the fax transmission.



## Receiving with Distinctive Ring Service

The unit has been equipped with a ring pattern detection feature, which allows you to have more effective use of the distinctive ring service provided by some telephone companies.

The distinctive ring service gives you up to 3 phone numbers on your single telephone line, each with a different ringing pattern. You may use one of the phone numbers as a facsimile telephone number. With the ring pattern detection feature, the unit will detect its own distinctive ringing pattern and automatically activate the fax function to receive documents.

If other calls come in, the unit will answer in the receiving mode selected by the RECEIVE MODE button.

When you set the distinctive ring feature, the FAX RING COUNT which determines the number of rings before the unit answers a distinctive ring call is set to "1" automatically. To change the number of rings before the unit answers a distinctive ring call, change the FAX RING COUNT (see page 24) after setting the distinctive ring feature.

■ The table below shows how the unit will answer incoming calls.

| Receiving call  | Receiving mode of the unit   |  |  |   |
|---|--|--|--|---|
|   | EXT. TAM   | TEL/FAX  | FAX  | TEL   |
| A call matching the selected distinctive ring pattern | The facsimile unit will activate the fax function.   | The facsimile unit will activate the fax function. | The facsimile unit will activate the fax function. | The facsimile unit will ring until you pick up.<br>If you do not answer the call by 15 rings, the unit will automatically switch to the TEL/FAX mode and answer depending on the ring type. |
| Other call  | The telephone answering machine or the facsimile unit will activate depending on an incoming call. | The facsimile unit will ring until you pick up.    | The facsimile unit will activate the fax function. |   |

### Note:

- When receiving a normal ring call in EXT. TAM mode, the answering machine answers the incoming call to record a message. If the facsimile detects fax tones, the unit activates the fax function. If the answering machine does not answer a normal ring call for some reason, the facsimile unit will ring until you pick up.

## Programming the unit with distinctive ringing pattern \_\_\_\_\_

To activate the feature, you need to program the ringing pattern of the phone number to be used as a facsimile number.

Ringing patterns that can be programmed:










**A:** Standard ring

**B:** Double ring

**C:** Triple ring (Short-long-short)

**D:** Other triple ring

**OFF:** Turning off the ring pattern detection feature (initial setting)

|  |   |   |   |
|--|---|---|---|
| <p><b>1</b></p>   | <p>Press <b>MENU</b>.</p>        | <p><b>4</b></p>   | <p>Press <b>▲</b> or <b>▼</b> to select the desired mode.</p> |
| <p><b>2</b></p>   | <p>Press <b>#31</b>.</p>         | <p><b>5</b></p>   | <p>Press <b>START/SET</b> to store the setting.</p>           |
| <p><b>3</b></p>  | <p>Press <b>START/SET</b>.</p>  | <p><b>6</b></p>  | <p>Press <b>MENU</b> to end the program.</p>                  |

## Special Settings


### Logo print position



Your logo, telephone number, date, time and page number will be printed on the transmitted document from your unit in the following manner.



**OUT:** Outside of the transmitted document's paper size.





**IN:** Inside of the transmitted document's paper size.

**OFF:** Not printed.

- 1**  Press **MENU**.



- 2**  Press **#21**.




- 3**  Press **START/SET**.




- 4**  Press **▲** or **▼** to select the desired setting.
- 5**  Press **START/SET** to store your selection.
- 6**  Press **MENU** to end the program.



## Overseas transmission mode


You may experience difficulty in transmitting documents overseas. When this feature is set to on, it will become easy to send documents as the transmission speed is slowed down.



- 1**  Press **MENU**.


- 2**  Press **#23**.


- 3**  Press **START/SET**.


- 4**  Press **▲** or **▼** to select "ON".



—If this feature is not required, select "OFF".
- 5**  Press **START/SET** to store your selection.
- 6**  Press **MENU** to end the program.

—Start transmission procedure (see pages 16 and 17).

### Notes:

- After the transmission has completed, this feature is turned off automatically.
- When using this feature, transmission time will increase.

***Paper save reception/copy***

Use this feature when you wish to save a recording paper during fax reception or copying. With this feature, the unit will reduce the data and print it out in half in length.

**Important:**

- *This feature will not work,*
  - when receiving documents sent in fine resolution or other nonstandard resolution.
  - when making a copy in the fine, super fine or half tone resolution.

**Sample of paper save print:**







**Original document**

[illegible]

## Printed document

[illegible]

To activate this feature, proceed as follows:


- 1 Press **MENU**.  

  - 2 Press **#33**.  

  - 3 Press **START/SET**.  

  - 4 Press **▲** or **▼** to select "ON".  

  - 5 Press **START/SET** to store your selection.  

  - 6 Press **MENU** to end the program.  


## Extension copy






With this feature, the unit will copy a document twice in length.

We recommend that you use this feature when you received fax messages in the paper save reception (see page 45) and you wish to enlarge them.

### Sample of extended copy:



To make an extension copy, proceed as follows:

- |  |   |
|--|---|
| <p><b>1</b> </p> <p>Insert the documents<br/><b>FACE DOWN.</b></p>  | <p><b>4</b> </p> <p>Press <b>COPY</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             COPYING         </div> <p>—The unit will start printing.</p> |
| <p><b>2</b> </p> <p>Press <b>MENU</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             1.SYSTEM SET UP         </div> | <p><b>5</b> </p> <p>Press <b>MENU</b> to end the operation.</p>   |
| <p><b>3</b> </p> <p>Press <b>#34</b>.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             EXTENSION COPY         </div>   |   |

## Original mode

Use this feature when you need to transmit and copy a document with very faint writing or very dark writing. The following choices are available:










**NORMAL:** Used for a document with normal writing.

**LIGHT:** Used for a document with very faint writing.

**DARKER:** Used for a document with very dark writing.

These settings are available in the standard, fine and super fine resolutions.

Set this feature before starting transmission or copying by following steps below.














- 1  Press **MENU**.  

- 2  Press **#46**.  

- 3  Press **START/SET**.  

- 4  Press **▲** or **▼** to select the desired mode.
- 5  Press **START/SET** to store the setting.
- 6  Press **MENU** to end the program.

### Note:

- This feature will return to the normal mode after the transmission or copying has completed.

## Resetting the advanced features

Use this feature to return the advanced features of #21 through #46 (see page 27) to their initial settings.

- 1  Press **MENU**.  

- 2  Press **#80**.  

- 3  Press **START/SET**.  

- 4  Press **▲** or **▼** to select "YES".  

- 5  Press **START/SET**.  
  
—If this feature is not required, press the STOP button.
- 6  Press **START/SET** again.  

- 7  Press **MENU** to end the program.


## Voice Contact

You can have a voice conversation on the same call after fax transmission or reception is completed. This saves the extra expense and time of making a subsequent telephone call to discuss the information sent over the fax.

**Important:**

- This feature works only when the other party's unit is equipped with the voice contact/call reservation feature.

### Initiating voice contact



- 1 Press **SP-PHONE/VOICE STDBY** while transmitting or receiving documents.

VOICE STANDBY

—Your unit will call the other party with a distinctive ring.

- 2 When the other party answers, the unit will emit a distinctive ring. While ringing, press **SP-PHONE/VOICE STDBY** again or lift the handset to start speaking.

**Notes:**

- If you initiate voice contact while transmitting documents, you can speak after all the documents have been transmitted.
- If you initiate voice contact while receiving documents, you can speak after the current page of the documents is received.
- You can initiate the voice contact by lifting the handset during transmission or reception.
- If the other party does not answer, the line will be disconnected automatically.

### Receiving a request for voice contact

If the other party initiates voice contact, your unit will emit a distinctive ring after the transmission or reception is completed.

When a distinctive ring is heard, press **SP-PHONE/VOICE STDBY** or lift the handset, then start speaking.


**Note:**

- If you do not answer within 10 seconds of hearing the distinctive ring, the line will be disconnected automatically.



## TONE, FLASH and PAUSE Buttons

### TONE button




The TONE (\*) button is used when your line has a rotary pulse dial service. Pressing the button allows you to change temporarily from pulse to tone mode during a dialing operation.

When you hang up, the unit will automatically return to pulse mode.

**Note:**

- TONE can be stored into a phone number for automatic dialing.

### FLASH button




The FLASH button functions as the hookswitch on a regular phone. If you misdial or dial another phone number, press the FLASH button firmly. The call will be terminated and you will hear dial tone. You can then dial the next phone number.

Also pressing the FLASH button allows you to use special features of the host exchange (if connected) or local telephone company services. For further details, contact the supplier or your local telephone companies.

**Note:**


- FLASH can be stored into a phone number for automatic dialing.

### PAUSE button



Pressing the REDIAL/PAUSE button causes a dialing delay in the dialing sequence.

**Example-1:** When your unit is connected to a host exchange, insert a pause as follows to get an outside line.



**Example-2:** If a transmission error occurs frequently when making an overseas transmission, add two pauses at the end of the phone number.



**Note:**

- PAUSE can be stored into a phone number for automatic dialing.

# Printing Reports and Lists

You can get the following reports and lists from your unit. See pages 51 and 52 for sample reports and lists.

## Basic Feature List:

This provides you with the current settings of the basic programming features (#01 to #11).

## Advanced Feature List:

This gives you a list of the current settings of the advanced programming features (#21 to #80).

## Telephone Number List:

This is a list of phone numbers and station names that are stored for one-touch dialing and speed dialing.

## Journal Report:





This gives you a record of all transmissions and receptions (up to 35 fax communications). This report is useful for keeping telephone records or for verifying telephone charges.

This report can be printed automatically after every 35 fax communications (see page 53).

## Printer test list:

This allows you to check the print quality of your unit. If the test pattern has any blurred points or lines or dirty patterns, please clean the thermal head by following the instructions on page 59.

## How to print each report/list

|                 |   |   |   |   |  |  |  |
|-----------------|---|---|---|---|--|--|--|
| <p><b>1</b></p> |   | <p>Press <b>MENU</b> repeatedly until the following is displayed.</p> | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">3. PRINT LIST</div> | <p>For the journal report, press #4.</p>    | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">JOURNAL REPORT</div> |  |  |
| <p><b>2</b></p> |  | <p>For the basic feature list, press #1.</p>                          | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">BASIC LIST</div>    | <p>For the printer test list, press #5.</p> | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">PRINTER TEST</div>   |  |  |
|                 |   | <p>For the advanced feature list, press #2.</p>                       | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">ADVANCE LIST</div>  |   |  |  |  |
|                 |   | <p>For the telephone number list, press #3.</p>                       | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">TEL NO. LIST</div>  |   |  |  |  |
|                 |   |   |   | <p><b>3</b></p>                             |                          | <p>Press <b>START/SET</b> to start printing.</p> | <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">PRINTING</div> |
|                 |   |   |   | <p><b>4</b></p>                             |                          | <p>Press <b>MENU</b> to end the operation.</p>   |  |

## Sample reports and lists

### Basic feature list

| BASIC FEATURE LIST |                           |                      |                |
|--------------------|---------------------------|----------------------|----------------|
| NO.                | FEATURE                   | CURRENT SETTING      |                |
| #01                | SET DATE & TIME           | Jan. 01 1994 12:00AM |                |
| #02                | YOUR LOGO                 | Panasonic FAX SYSTEM |                |
| #03                | YOUR TELEPHONE NUMBER     |                      |                |
| #04                | PRINT TRANSMISSION REPORT | ERROR                | [ERROR,ON,OFF] |
| #06                | TEL/FAX DELAYED RING      | 1                    | [1...4]        |
| #07                | FAX RING COUNT            | 1                    | [1...4]        |
| #11                | REMOTE TAM ACT.           | OFF                  | [ON,OFF]       |
| ID = 11            |                           |                      |                |

### Advanced feature list

| ADVANCED FEATURE LIST |                             |                 |              |
|-----------------------|-----------------------------|-----------------|--------------|
| NO.                   | FEATURE                     | CURRENT SETTING |              |
| #21                   | LOGO POSITION               | OUT             | [OUT,IN,OFF] |
| #22                   | JOURNAL AUTO PRINT          | ON              | [ON,OFF]     |
| #23                   | OVERSEAS MODE               | OFF             | [ON,OFF]     |
| #24                   | JUNK MAIL PROHIBITOR        | OFF             | [ON,OFF]     |
| ID = 22               |                             |                 |              |
| #25                   | DELAYED TRANSMISSION        | OFF             | [ON,OFF]     |
| DESTINATION =         |                             |                 |              |
| START TIME = 12:00AM  |                             |                 |              |
| #30                   | SILENT FAX RECOGNITION RING | 3               | [3...6]      |

### Telephone number list

| TELEPHONE NUMBER LIST |           |                  |           |
|-----------------------|-----------|------------------|-----------|
| STATION KEY LIST      |           |                  |           |
| TELEPHONE NUMBER      | NAME      | TELEPHONE NUMBER | NAME      |
| 01 092-123-4567       | COMPANY A | 06 999-1234      |           |
| 02 83-555-1234        | COMPANY B | 07 [ ]           |           |
| 03 012-999-8877       | COMPANY C | 08               |           |
| 04 83P4567            |           | 09               |           |
| 05 987-6543           |           | 10               |           |
| AUTO KEY LIST         |           |                  |           |
| TELEPHONE NUMBER      | NAME      | TELEPHONE NUMBER | NAME      |
| 00 111-2233*123       |           | 11 222-3344      | COMPANY D |
| 01 765-4321           |           | 12 092-555-6677  | COMPANY E |
| 02 345F6789           |           | 13               |           |
| 03 092( )             |           | 14               |           |
| 04                    |           | 15               |           |
| 05                    |           | 16               |           |

#### Codes in each phone number

\*: \* has been entered.

P: The pause has been entered.

F: The flash has been entered.

-: The hyphen has been entered.

[ ]: The secret phone number has been entered.  
(The telephone number is not printed.)

## Journal report

| JOURNAL              |                 |                 |            |      |       |                     |      |
|----------------------|-----------------|-----------------|------------|------|-------|---------------------|------|
| Jan. 01 1994 06:05PM |                 |                 |            |      |       |                     |      |
| NO.                  | OTHER FACSIMILE | START TIME      | USAGE TIME | MODE | PAGES | RESULT              | CODE |
| 01                   | 1234567         | Jan. 01 11:28AM | 01'20      | TX   | 02    | OK                  |      |
| 02                   | 9998765         | Jan. 01 11:52AM | 00'56      | TX   | 01    | OK                  |      |
| 03                   | << G3 >>        | Jan. 01 11:58AM | 00'32      | RX   | 01    | OK                  |      |
| 04                   | 555556677       | Jan. 01 00:19PM | 01'48      | TX   | 03    | OK                  |      |
| 05                   | +987 1234       | Jan. 01 00:35PM | 01'42      | RX   | 03    | OK                  |      |
| 06                   | <S01>           | Jan. 01 01:14PM | 02'40      | TX   | 05    | OK                  |      |
| 07                   | 7776543         | Jan. 01 01:27PM | 01'03      | TX   | 01    | OK                  |      |
| 08                   | 4445566         | Jan. 01 02:46PM | 01'18      | TX   | 02    | OK                  |      |
| 09                   | <A17>           | Jan. 01 03:17PM | 00'35      | TX   | 00    | COMMUNICATION ERROR | (71) |
| 10                   | << G3 >>        | Jan. 01 03:19PM | 01'21      | RX   | 03    | OK                  |      |
| 11                   | 6667788         | Jan. 01 03:38PM | 02'25      | TX   | 04    | OK                  |      |
|                      |                 |                 |            | TX   | 01    | OK                  |      |
|                      |                 |                 |            | TX   | 02    | OK                  |      |

- ① Communication mode:  
 TX...Transmission  
 RX...Reception  
 POL.TX...Polling transmission  
 POL.RX...Polling reception
- ② Number of pages received or transmitted successfully
- ③ Communication result  
 (For the explanation of communication results, see page 56.)
- ④ Error code (for the service personnel use only)

## Print test list


## Setting journal auto print

This feature allows the unit to print a record of the last 35 fax communications (transmissions and receptions) automatically.


After printing, memory will clear and the unit will begin to store new data of the journal report.

When this feature is deactivated, the journal report data is stored until the memory becomes full. When memory is full and a new communication takes place, the oldest data will be erased and the newest data will be stored.


To activate this feature, proceed as follows.

- 


Press **MENU**.


1.SYSTEM SET UP
- 


Press #, then press 22.

AUTO JOURNAL
- 

Press **START/SET**.

MODE=ON [▲▼]
- 

Press ▲ or ▼ to select the desired mode.
- 

Press **START/SET** to store the setting.
- 

Press **MENU** to end the program.

# Troubleshooting

## Error messages on the display

If the unit detects a problem, one of the following messages will appear on the display.

| ERROR MESSAGE   | CAUSE AND REMEDY   |
|-----------------|--|
| CHECK COVER     | <ul style="list-style-type: none"> <li>•The top cover is open. Close it.</li> </ul>  |
| CHECK DOCUMENT  | <ul style="list-style-type: none"> <li>•The document is not fed into the unit properly. Re-insert the document. If the misfeeding occurs frequently, clean the document feeder rollers and the sub roller inside the unit (see page 59). Still it remains unsolved, adjust the feeder pressure (see page 58).</li> </ul> |
| CHECK MEMORY    | <ul style="list-style-type: none"> <li>•Memory (phone numbers, parameters, etc.) has been erased. Re-program them.</li> </ul>  |
| MECHA ERROR     | <ul style="list-style-type: none"> <li>•Mechanical error occurs. Open the cover and re-install the recording paper. Then press the STOP button and close the cover.</li> </ul>   |
| NO RESPONSE     | <ul style="list-style-type: none"> <li>•The receiving unit is busy or out of recording paper. Try again.</li> </ul>  |
| OUT OF PAPER    | <ul style="list-style-type: none"> <li>•The unit ran out of recording paper. Replace it (see page 8).</li> </ul>   |
| PAPER JAMMED    | <ul style="list-style-type: none"> <li>•The recording paper is jammed. Clear the jammed paper (see page 57).</li> </ul>  |
| POLLING ERROR   | <ul style="list-style-type: none"> <li>•The other unit does not provide the polling function. Check the other party.</li> </ul>  |
| REMOVE DOCUMENT | <ul style="list-style-type: none"> <li>•The document is jammed. Open the cover, remove the jammed document (see page 58) and try again.</li> <li>•Attempted to transmit a document longer than 600 mm (23<sup>5</sup>/<sub>8</sub>" ). Press the STOP button and remove it (see page 58).</li> </ul>                     |
| TRANSMIT ERROR  | <ul style="list-style-type: none"> <li>•Transmission error occurs. Try again.</li> </ul>   |
| UNIT OVERHEATED | <ul style="list-style-type: none"> <li>•The unit is too hot. Leave it as it is and allow it to cool down.</li> </ul>   |

## General corrective measures

---

### GENERAL

---

**I cannot make and receive calls.**

- The line cord is connected incorrectly or not connected. Confirm the connection (see page 9).

**I cannot make calls.**

- The setting of the dialing mode is wrong. Check the selector (see page 9).

**The unit does not work.**

- Disconnect the unit from the telephone line and connect a known working phone. If the known working phone operates properly, call your service personnel to have the unit repaired. If the known working phone does not operate properly, consult your telephone company.

**The unit does not ring.**

- The ringer volume is set to OFF. Raise it to a suitable level (see page 10).

**The REDIAL/PAUSE button does not function properly.**

- The button has combination feature of redial and pause. It will redial the last dialed number when it is pressed after hanging up and getting dial tone again (see page 13). If it is pressed after you dial another phone number, the button will function as pause button (see page 49).

**While programming, I cannot enter the code or ID number.**

- The whole or part of the number you try to enter is same as the other code or ID. Change the number into new one (see pages 20, 38 and 39).

### FAX TRANSMISSION

---

**The other party complains that letters on their received document are distorted.**

- If your line has special telephone services such as call waiting, the service may have been activated during the fax reception. Connect the unit to a line that does not have such services.
- Another telephone connected to the same line as your unit is connected is hung off. Hang up and try again.

**The other party complains that dirty patterns or black line appear on their received documents.**

- The glass or rollers on your unit are dirty. Clean them (see page 59).

**I cannot make an international fax call.**

- Use the overseas transmission mode (see page 44).
- Add two pauses at the end of the phone number (see page 49).

### FAX RECEPTION

---

**I cannot receive documents automatically.**

- The receive mode is set to *TEL*. Set the receive mode to *EXT. TAM*, *TEL/FAX* or *FAX*.
- The time to answer the call may be too long. Decrease the number of rings (see pages 23 and 24).

**Recording image is faint.**

- The sender transmitted a faint document. Request them to transmit a clearer copy of the document.
- The thermal head is dirty. Clean it (see page 59).

### RECEPTION IN EXT. TAM MODE

---

**I cannot receive documents automatically.**

- Your greeting message on the answering machine may be too long. Shorten the message (up to 10 seconds) or ask the other party to press your remote fax activation code and then start transmission (see page 37).
- Set the number of rings to one or two on the answering machine.
- The silent detection feature is set to OFF. Set it to ON (see page 21).

**I cannot receive voice messages.**

- Confirm that the answering machine is turned on or connected to the unit properly.
- Set the number of rings to one or two on the answering machine.

## ***RECEPTION IN EXT. TAM MODE (cont.)***

**I cannot retrieve messages remotely from the answering machine.**

- Your remote TAM activation code on the answering machine may be same as your remote fax activation code or junk mail prohibitor ID. Set a different number in each code/ID. Also set the same remote TAM activation code as stored on the answering machine into the unit's memory (see page 20).

**The greeting message on the answering machine stop halfway and the caller cannot leave a voice message.**

- Make sure that the greeting message does not have a silent pause longer than 4 seconds. If so, re-record the greeting message.

**When I tried to operate the answering machine remotely, the line was disconnected after pressing the remote access code.**

- The code may include # which is used for some features provided by telephone companies. Change the code on the answering machine into another number which does not include #, then program the same code into the facsimile unit (see page 20).

## ***COPYING***

**Dirty patterns or black line appear on the copied documents.**

- The glass or rollers on your unit are dirty. Clean them (see page 59).

**Copied image is distorted.**

- The thermal head is dirty. Clean it (see page 59).

## ***Explanation of communication result on the report***





When trouble occurs, the following messages may be printed on the transmission report and the journal report.

| <b><i>PRINTED MESSAGE</i></b> | <b><i>MEANING</i></b>  |
|-------------------------------|--|
| COMMUNICATION ERROR:          | ●Transmission or reception error occurred. Try again or check the other party. |
| DOCUMENT JAMMED:              | ●A document was jammed. Remove the jammed document (see page 58).              |
| JUNKMAIL PROH. REJECT:        | ●The unit rejected fax reception when the junk mail prohibitor is activated.   |
| NO DOCUMENT:                  | ●The document was not fed into the unit properly.                              |
| NO RESPONSE:                  | ●The receiving unit is busy or out of recording paper. Try again.              |
| PAPER JAMMED:                 | ●The recording paper was jammed.   |
| PAPER OUT:                    | ●The unit was out of recording paper.  |
| PRESSED THE STOP KEY:         | ●The fax communication was interrupted because the STOP button was pressed.    |
| PRINTER OVERHEATED:           | ●Printer was overheated.   |
| THE COVER WAS OPENED:         | ●The top cover was open.   |
| OK:                           | ●Fax communication was successful.   |



## Clearing a recording paper jam


When the unit does not eject a recording paper during reception or copying, the recording paper has jammed. Remove the jammed paper by following the steps below.



- 1 Slide the lever toward you to open the top cover.
- 2 Remove the jammed paper carefully.
- 3 Cut off the wrinkled portion.
- 4 Replace the recording paper roll in the proper direction.  
—Make sure that there is no slack in the paper roll.
- 5 Insert the leading edge of the paper under the green bar.  
—If the recording paper cannot be inserted, press the STOP button to reset the paper cutter and insert the paper again.
- 6 Close the cover carefully by gently pushing down on both ends.

## Clearing a document jam


When an original document becomes jammed, remove the jammed document by following the steps below.



- 1 Slide the lever toward you to open the top cover.
- 2 Remove the jammed document carefully.
- 3 Close the cover carefully by gently pushing down on both ends.

## Adjusting the feeder pressure

If misfeeding of documents, such as multiple feeding or no feeding, occurs frequently, try to adjust the feeder pressure by following the steps below.




- 1 Open the top cover.
- 2 Shift the position of the lever by using an instrument with a pointed end, like a clip or ball-point pen.  
  
Position A: The case of no feeding  
Position B: Standard position  
Position C: The case of multiple feeding
- 3 Close the top cover carefully by gently pressing down on both ends.

## Maintenance

### Cleaning the document feeder unit


When the misfeeding occurs frequently or when dirty patterns or black bands appear on a copied or transmitted document, clean the sub roller, the document feeder rollers and the glass by following the steps below.



- ❶ Disconnect the power cord and the telephone line cord.
- ❷ Slide the lever toward you to open the top cover.
- ❸ Clean the rubber, the sub roller and the document feeder rollers rotating them with a cloth moistened with isopropyl rubbing alcohol, then dry thoroughly.
- ❹ Clean the glass and the white plate with a dry soft cloth.
- ❺ Close the top cover carefully by gently pressing down on both ends.
- ❻ Connect the power cord and telephone line cord.

### Cleaning the thermal head

If dirty patterns or black bands appear on a copied or received document, clean the thermal head by following the steps below.



- ❶ Disconnect the power cord and the telephone line cord.
- ❷ Slide the lever toward you to open the top cover.
- ❸ Remove the recording paper roll from the unit.
- ❹ Clean the thermal head with a cloth moistened with isopropyl rubbing alcohol, then dry thoroughly.
- ❺ Re-install the recording paper roll, then close the top cover carefully by gently pressing down on both ends.
- ❻ Connect the power cord and telephone line cord.

**Note:**

- To prevent malfunction due to static electricity, do not use a dry cloth and do not touch the thermal head directly with your finger.

## Important Safety Instructions

When using this unit, basic safety precautions as below should always be followed to reduce the risk of fire, electric shock, or personal injury.

1. Read and understand all instructions.
2. Follow all warnings and instructions marked on this unit.
3. Unplug this unit from wall outlets before cleaning. Do not use liquid or aerosol cleaners. Use a damp cloth for cleaning.
4. Do not use this unit near water, for example, near a bath tub, wash bowl, kitchen sink, or the like.
5. Install this unit securely on a stable surface. Serious damage may result if the unit falls.
6. Do not cover slots and openings of the unit, for they are provided for ventilation and protection against overheating. Never place the unit near radiators, in/or a place where proper ventilation is not provided.
7. Use only the power source as marked on the unit. If you are not sure of the type of the power supply to your home, consult your dealer or local power company.
8. Do not place objects on the power cord. Install the unit where no one can step on the cord.
9. Do not overload wall outlets and extension cords as this can result in the risk of fire or electric shock.
10. Never push any objects into this unit through slots as they may result in risk of fire or electric shock. Never spill any liquid on the unit.
11. To reduce the risk of electric shock, do not disassemble this unit, but take it to a qualified serviceman when some service or repair work is required. Opening or removing covers may expose you to dangerous voltages or other risks. Incorrect reassembly can cause electric shock when the appliance is subsequently used.
12. Unplug this unit from the wall outlet and refer servicing to qualified service personnel under the following conditions:
  - A. When the power supply cord or plug is damaged or frayed.
  - B. If liquid has been spilled into the unit.
  - C. If the unit has been exposed to rain or water.
  - D. If the unit does not work normally by following the operating instructions. Adjust only controls covered by the operating

instructions, for improper adjustment may require extensive work by a qualified technician.

- E. If the unit has been dropped or damaged.
- F. If the unit exhibits a distinct change in performance.
13. During thunderstorms, avoid using telephones except cordless types. There may be a remote risk of electric shock from lightning.
14. Do not use this unit to report a gas leak in the vicinity of it.

## SAVE THESE INSTRUCTIONS

### INSTALLATION:

1. Never install telephone wiring during a lightning storm.
2. Never install telephone jacks in wet locations unless the jack is specifically designed for wet locations.
3. Never touch uninsulated telephone wires or terminals unless the telephone line has been disconnected at the network interface.
4. Use caution when installing or modifying telephone lines.

### WARNING:

To prevent fire or shock hazard, do not expose this product to rain or any type of moisture.

## Other Information

- Keep the unit away from electrical noise-generating devices, such as fluorescent lamps and motors.
- The unit should be kept free from dust, moisture, high temperature, and vibration.
- The unit should not be exposed to direct sunlight.
- Do not place heavy objects on top of this unit.
- Do not use benzine, thinner, or any abrasive powder, to clean the cabinet. Wipe it with a soft cloth.
- Do not damage the power cord.  
Do not touch the plug with wet hands.

## Accessory Order Information

Use the following type of recording paper for replacement. For accessory order, call toll free 1-800-332-5368.

| Parts No. | Description   | Comment                     |
|-----------|---|-----------------------------|
| KX-A116   | Standard Thermal Recording Paper                    | 216 mm×50 m (8½"×164') roll |
| KX-A106   | Standard Thermal Recording Paper                    | 216 mm×30 m (8½"×98') roll  |
| KX-A125   | Super Thermal Recording Paper<br>(Plain paper like) | 216 mm×30 m (8½"×98') roll  |

## Specifications

1. **Applicable Lines:** Public Switched Telephone Network
2. **Document Size:** Max. 216 mm (8½") in width  
Max. 600 mm (23⅝") in length
3. **Effective Scanning Width:** 208 mm (8⅜")
4. **Printing Paper Size:** (See Accessory Order Information on this page)
5. **Effective Printing Width:** 208 mm (8⅜")
6. **Transmission Time\*:** Approx. 15 sec/page (Original mode)  
Approx. 30 sec/page (G3 Normal mode)
7. **Fax Auto Redial:** Up to 5 times
8. **Telephone Auto Redial:** Up to 14 times
9. **Scanning Density:** Horizontal 8 pels/mm (203 pels/inch)  
Vertical 3.85 lines/mm (98 lines/inch)—Standard  
7.7 lines/mm (196 lines/inch)—Fine/Halftone  
15.4 lines/mm (392 lines/inch)—Superfine
10. **Scanner Type:** CCD image sensor
11. **Printer Type:** Thermal printing
12. **Data Compression System:** Modified Huffman (MH), Modified READ (MR)
13. **Modem Speed:** 9600/7200/4800/2400 bps; Automatic Fallback
14. **Operating Environment:** 5–35°C (41–95°F), 45%–85% RH
15. **Dimensions (H×W×D):** 122×362×287 mm (4⅓×14¼×11⅝")
16. **Mass (Weight):** Approx. 3.9 kg (8.6 lb.)
17. **Power Consumption:** Transmission: Approx. 15 W / Reception: Approx. 35 W  
Copy: Approx. 40 W / Standby: Approx. 5 W  
Maximum: Approx. 100 W
18. **Power Supply:** 120 V AC, 60 Hz

\*Transmission Time: Transmission times apply to text data using the ITU-T No. 1 test chart, between the same machine models at maximum modem speed. Transmission times vary in actual usage.

## FCC Information

If required by the telephone company, inform them of the following.

- FCC Registration No.: (found on the rear side of the unit)
- Ringer Equivalence No.: (found on the rear side of the unit)
- The particular telephone line to which the equipment is connected.

This unit must not be connected to a coin operated line. If you are on a party line, check with your local telephone company.

### **Ringer Equivalence Number (REN):**

This REN is useful in determining the quantity of devices you may connect to your telephone line and still have all of those devices ring when your telephone number is called. In most but not all areas, the sum of the REN's of all devices connected to one line should not exceed five (5.0). To be certain of the number of devices you may connect to your line, as determined by the REN, you should contact your local telephone company to determine the maximum REN for your calling area.

In the event that terminal equipment causes harm to the telephone network, the telephone company should notify the customer, if possible, that service may be stopped. However, where prior notice is impractical, the company may temporarily cease service providing that they:

- a) Promptly notify the customer.
- b) Give the customer an opportunity to correct the problem with their equipment.
- c) Inform the customer of the right to bring a complaint to the Federal Communication Commission pursuant to procedures set out in FCC Rules and Regulations Subpart E of Part 68.

The Telephone Company may make changes in its communications facilities, equipment operations, or procedures where such action is reasonably required in the operation of its business and is not inconsistent with the rules and regulations in FCC Part 68. If such changes can be reasonably expected to render any customer terminal equipment incompatible with telephone company communications facilities, or require modification

or alteration of such terminal equipment, or otherwise materially affect its use or performance, the customer shall be given adequate notice in writing, to allow the customer an opportunity to maintain uninterrupted service.

### **CAUTION:**

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this device.

When programming emergency numbers and/or making test calls to emergency numbers:

1. Remain on the line and briefly explain to the dispatcher the reason for the call before hanging up.
2. Perform such activities in the off-peak hours; such as early morning or late evenings.

This telephone provides magnetic coupling to hearing aids.

### **Note:**

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## Limited Warranty

### PANASONIC PERSONAL FACSIMILE Limited Warranty

Matsushita Consumer Electronics Company or Panasonic Sales Company (collectively referred to as "The warrantor"), will repair this product with new or refurbished parts, free of charge, in the U.S.A. or Puerto Rico for one (1) year from the date of original purchase in the event of a defect in materials or workmanship.

**Batteries (when applicable)**—New rechargeable batteries in exchange for defective rechargeable batteries for ten (10) days from the date of original purchase. Non-rechargeable batteries are not warranted.

Carry-in or mail-in service in the U.S.A. can be obtained during the warranty period from a Matsushita Services Company (MSC) Factory Servicenter listed in the Servicenter Directory. Carry-in or mail-in service in Puerto Rico can be obtained during the warranty period by calling the telephone numbers listed in the Servicenter Directory.

This warranty is extended only to the original purchaser. A purchase receipt or other proof of date of original purchase will be required before warranty performance is rendered.

This warranty only covers failures due to defects in materials or workmanship which occur during normal use. It does not cover damage which occurs in shipment or failures which are caused by products not supplied by the warrantor or failures which result from accident, misuse, abuse, neglect, mishandling, misapplication, alteration, faulty installation, modification, or service by anyone other than an MSC Factory Servicenter or an authorized MSC Servicenter or damage that is attributable to Acts of God, including, but not limited to, line surges.

#### LIMITS AND EXCLUSIONS

There are no express warranties except as listed above.

THE WARRANTOR SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, INCLUDING, WITHOUT LIMITATION, LOSS OF GOODWILL, PROFITS OR REVENUE, LOSS OF USE OF THIS PRODUCT OR ANY ASSOCIATED EQUIPMENT, COST OF SUBSTITUTE EQUIPMENT, DOWNTIME COSTS, OR CLAIMS OF ANY PARTY DEALING WITH BUYER FOR SUCH DAMAGES, RESULTING FROM THE USE OF THIS PRODUCT OR ARISING FROM BREACH OF WARRANTY OR CONTRACT, NEGLIGENCE, OR ANY OTHER LEGAL THEORY.

ALL EXPRESS AND IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED TO THE APPLICABLE WARRANTY PERIOD SET FORTH ABOVE.

Some states do not allow the exclusion or limitation of consequential damages, or limitations on how long an implied warranty lasts, so the above exclusions or limitations may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

If a problem with this product develops during the warranty period, you may contact your dealer or the MSC Factory Servicenter or authorized MSC servicenter. If the problem is not handled to your satisfaction, write to the Customer Satisfaction Center at the address indicated on the Servicenter Directory.

# Index

|          |                                      |                |          |                                   |            |
|----------|--------------------------------------|----------------|----------|-----------------------------------|------------|
| <b>A</b> | Advanced feature list .....          | 50             | <b>O</b> | One-touch dialing .....           | 12, 17, 32 |
|          | Automatic dialing .....              | 12, 17, 32     |          | Original mode .....               | 47         |
| <b>B</b> | Basic feature list .....             | 50             |          | Overseas transmission mode .....  | 44         |
| <b>C</b> | Cleaning .....                       | 59             | <b>P</b> | Paper save .....                  | 45         |
|          | COPY .....                           | 25             |          | PAUSE .....                       | 49         |
| <b>D</b> | Date and time .....                  | 30             |          | Polled .....                      | 35         |
|          | Delayed transmission .....           | 36             |          | Polling .....                     | 35         |
|          | DELETE .....                         | 29             |          | Printer test list .....           | 50         |
|          | Dial keypad .....                    | 28             | <b>R</b> | RECEIVE MODE .....                | 11         |
|          | Dialing mode .....                   | 9              |          | REDIAL/PAUSE .....                | 13         |
|          | Direct call station keys .....       | 12, 17, 29, 32 |          | Remote fax activation code .....  | 37, 38     |
|          | DIRECTORY .....                      | 12, 17, 34     |          | Remote TAM activation ID .....    | 20         |
| <b>E</b> | Electronic telephone directory ..... | 34             |          | RESOLUTION .....                  | 15         |
|          | Error messages .....                 | 54             |          | Ringer volume .....               | 10         |
|          | Extension copy .....                 | 46             |          | Ring pattern detection .....      | 42         |
|          | EXT. TAM mode .....                  | 11, 18         | <b>S</b> | SECRET .....                      | 33         |
| <b>F</b> | FAX mode .....                       | 11, 24         |          | SET DEFAULT .....                 | 47         |
|          | FAX ring .....                       | 24             |          | Silent detection .....            | 21         |
|          | Feeder pressure .....                | 58             |          | Silent fax recognition ring ..... | 23         |
|          | FLASH .....                          | 12, 49         |          | SPACE .....                       | 29         |
| <b>H</b> | Handset volume .....                 | 10             |          | Speaker volume .....              | 10         |
|          | HELP .....                           | 3              |          | Speed dialing .....               | 12, 17, 33 |
| <b>I</b> | INSERT .....                         | 29             |          | SP-PHONE .....                    | 12, 48     |
| <b>J</b> | Journal auto print .....             | 53             |          | START/SET .....                   | 16, 20     |
|          | Journal report .....                 | 50             |          | STOP .....                        | 16         |
|          | Junk mail prohibitor .....           | 39             | <b>T</b> | TEL mode .....                    | 11         |
|          | Junk mail prohibitor ID .....        | 39, 40         |          | TEL/FAX mode .....                | 11, 22     |
| <b>L</b> | Logo position .....                  | 43             |          | TEL/FAX ring .....                | 23         |
|          | LOWER .....                          | 12, 17, 32     |          | Telephone number list .....       | 50         |
| <b>M</b> | MENU .....                           | 20, 30, 35, 50 |          | TONE .....                        | 49         |
|          | MUTE .....                           | 13             |          | TONE/PULSE .....                  | 9          |
|          |                                      |                |          | Transmission report .....         | 31         |
|          |                                      |                | <b>V</b> | VOLUME .....                      | 10         |
|          |                                      |                | <b>Y</b> | Your logo .....                   | 30         |
|          |                                      |                |          | Your telephone number .....       | 31         |



# FAX CORRESPONDENCE

TO: \_\_\_\_\_ DATE: \_\_\_\_\_

FROM: \_\_\_\_\_ OUR TEL. NO.: \_\_\_\_\_

We have Panasonic personal facsimile and a telephone answering machine is connected. So you can send both documents and voice messages on the same call.

## Leaving a voice message and transmitting a document

1. Dial our phone number.
  - Our telephone answering machine will play the greeting message.
2. Leave your message after the long beep.
3. Press your “\*” (asterisk) button **twice** to activate the fax reception.
  - A fax tone will sound.
4. Start transmission to send a fax.

## Transmitting a document only

1. Dial our phone number.
  - Our telephone answering machine will play the greeting message.
2. Press your “\*” button **twice** while the greeting message is being played.
  - A fax tone will sound.
3. Start transmission to send a fax.

## Transmitting a document from a rotary (pulse) phone

1. Dial our phone number.
  - Our telephone answering machine will play the greeting message.
2. Start transmission to send a fax while the greeting message is being played.

### Notes:

- If you wish to receive voice messages and documents automatically, the following preparations are necessary.
  - Connect a telephone answering machine to the unit and activate the answering function.
  - Set the unit in EXT. TAM mode.
- “\* button **twice**” is called remote fax activation code (see page 38). If you change it into another one, inform callers of pressing the code.

## Speed dialer list

| Station No. | Name/Phone No. | Station No. | Name/Phone No. |
|-------------|----------------|-------------|----------------|
| 00          |                | 11          |                |
| 01          |                | 12          |                |
| 02          |                | 13          |                |
| 03          |                | 14          |                |
| 04          |                | 15          |                |
| 05          |                | 16          |                |
| 06          |                | 17          |                |
| 07          |                | 18          |                |
| 08          |                | 19          |                |
| 09          |                | 20          |                |
| 10          |                | 21          |                |

# Servicenter directory

## PRODUCT INFORMATION • OPERATION ASSISTANCE • LITERATURE REQUESTS • DEALER LOCATIONS

**DIAL TOLL FREE: 1-800-HELP-FAX**

Customer Satisfaction Center 2F-3, One Panasonic Way, Secaucus, NJ 07094 (Headquarters)  
201-348-9090 (9:00am–8:00pm Monday–Friday, EST)

## AUTHORIZED SERVICENTERS • PARTS DISTRIBUTOR LOCATIONS

To locate an independent authorized servicenter or parts distributor in your area, within the USA dial toll free **1-800-545-2672**, 24 hours a day, 7 days a week.

### PRODUCT REPAIRS Factory Servicenters

#### CALIFORNIA

6550 Katella Avenue  
Cypress, CA 90630  
Phone (714) 373-7425  
Fax (714) 894-8534

800 Dubuque Avenue  
So. San Francisco,  
CA 94080  
Phone (415) 871-6373  
Fax (415) 871-6840

20201 Sherman Way  
Suite 102  
Canoga Park, CA 91306  
Phone (818) 709-1775  
Fax (818) 709-2165

3878 Ruffin Road  
Suite A  
San Diego, CA 92123  
Phone (619) 560-9200  
Fax (619) 560-1831

#### COLORADO

1640 South Abilene Suite D  
Aurora, CO 80012  
Phone (303) 752-2024  
Fax (303) 752-0610

#### FLORIDA

3700 North 29th Avenue  
Suite 102  
Hollywood, FL 33020  
Phone (305) 925-2880  
Fax (305) 925-5224

4710 Eisenhower  
Boulevard Suite A1  
Tampa, FL 33634  
Phone (813) 884-4746  
Fax (813) 886-4564

#### GEORGIA

4245 International Boulevard  
Suite C  
Norcross, GA 30093  
Phone (404) 717-6880  
Fax (404) 717-6668

#### HAWAII

99-859 Iwaiwa Street  
Aiea, Hawaii 96701  
Phone (808) 488-1996  
Fax (808) 486-4369

#### ILLINOIS

•1703 North Randall Road  
Elgin, IL 60123  
"12:30 to 4:30, Mon-Fri"  
Phone (708) 468-5466  
Fax (708) 468-5465

9060 Golf Road  
Niles, IL 60714  
Phone (708) 299-1700  
Fax (708) 299-1710

#### MARYLAND

Sulphur Springs  
Business Center  
1638 Sulphur Springs Road  
Baltimore, MD 21227  
Phone (410) 242-2607  
Fax (410) 247-3047

#### MASSACHUSETTS

60 Glacier Drive, Suite G  
Westwood, MA 02090  
Phone (617) 329-4280  
Fax (617) 329-0586

•pick-up/drop-off only

#### MICHIGAN

37048 Van Dyke Avenue  
Sterling Heights, MI 48312  
Phone (810) 939-2060  
Fax (810) 939-2638

#### MINNESOTA

7850-12th Avenue South  
Airport Business Center  
Bloomington, MN 55425  
Phone (612) 854-8624  
Fax (612) 854-2089

#### MISSOURI

11982 Dorsett Road  
Maryland Heights, MO 63043  
Phone (314) 739-5301  
Fax (314) 739-3631

#### OHIO

2236 Waycross Road  
Cincinnati, OH 45240  
Phone (513) 851-4180  
Fax (513) 851-8443

#### PENNSYLVANIA

2221 Cabot Boulevard West  
Suite B  
Langhorne, PA 19047  
Phone (215) 741-0661  
Fax (215) 741-0521

Campbell's Run  
Business Center  
500 Business Center Drive  
Pittsburgh, PA 15205  
Phone (412) 788-2174  
Fax (412) 788-2176

#### TENNESSEE

919-8th Avenue South  
Nashville, TN 37203  
Phone (615) 244-4434  
Fax (615) 244-6713

#### TEXAS

7482 Harwin Drive  
Houston, TX 77036  
Phone (713) 781-1528  
Fax (713) 781-0643

13615 Welch Road Suite 101  
Farmers Branch, TX 75244  
Phone (214) 385-1975  
Fax (214) 960-7626

#### WASHINGTON

20425-84th Avenue South  
Kent, WA 98032  
Phone (206) 872-7922  
Fax (206) 872-0918

### Service in Puerto Rico

**Matsushita Electric  
of Puerto Rico, Inc.  
Panasonic Sales Company/  
Factory Servicenter**

Ave. 65 de Infantería, Km. 9.5  
San Gabriel Industrial Park  
Carolina, Puerto Rico 00985  
Phone (809) 750-4300  
Fax (809) 768-2910

### REPAIR INQUIRIES Regional Customer Care Department

#### EAST (PCE)

2221 Cabot Boulevard West  
Suite A  
Langhorne, PA 19047  
Phone (215) 741-0676  
Fax (215) 750-6492

#### Covers:

CT, DE, ME, MD, MA,  
NH, NJ, NY, PA, RI, VT,  
VA, DC, WV

#### EAST (PCE)

1854 Shackelford Court  
Suite 4105  
Norcross, GA 30093  
Phone (404) 717-6860  
Fax (404) 717-6678

#### Covers:

AL, FL, GA, MS, NC, SC, TN

#### CENTRAL (PCC)

1703 North Randall Road  
Elgin, IL 60123  
Phone (708) 468-5530  
Fax (708) 468-5528

#### Covers:

AR, IL, IN, IA, KS, KY, LA,  
MI, MN, MO, NE, ND, OK,  
SD, TX, WI, OH

#### WEST (PCW)

6550 Katella Avenue  
Cypress, CA 90630  
Phone (714) 373-7440  
Fax (714) 373-7447

#### Covers:

AK, AZ, CA, CO, ID, MT, NV,  
NM, OR, UT, WA, WY, HI

### ACCESSORY PURCHASES

**1-800-332-5368** (Consumer Orders Only)

**Matsushita Services Company** Box 01, 545 Tollgate Road Suite C, Elgin, IL 60123  
(8:00am–7:30pm Monday–Thursday; 8:00am–5:00pm Friday; 9:00am–12:30pm Saturday; CST)  
(Visa, Mastercard, Discover card, Check or Money Order)

(940905)

## FAX ADVANTAGE PROGRAM

**We are proud to present the Panasonic Fax Advantage Program. It's an incredible service program that's full of exciting advantages!**

### Customer Satisfaction

In support of our one-year limited warranty\* (parts and labor) on our current fax product line, Panasonic is proud to offer you the following service options during the limited warranty period:

- 1 If you mail-in or carry-in your fax unit to one of our Regional Servicenters, the product will be repaired and returned to you, or...
- 2 If you call our 1-800-HELPFAX toll-free number, you will receive a refurbished replacement product overnight or on the second business day (delivery depending on the time of your call.)

### Support After The Sale

If you have a problem with your fax, just call our 1-800-HELPFAX toll-free number for friendly support and assistance. We have a highly-qualified team of experts who can diagnose, and most likely solve, your problem over the phone. Approximately 90% of our customers' problems are resolved with just a simple phone call.

The Fax Advantage Program covers the first year of purchase and works like this:

- 1 If you have a problem with your fax, call toll-free 1-800-HELPFAX.
- 2 Talk to one of our experienced technical experts to diagnose (and most likely solve) your problem over the phone.
- 3 Providing that you may be entitled to Panasonic's service under the terms and conditions of the limited warranty\*\*, we will arrange for a reconditioned replacement unit to be shipped to you overnight or second business day delivery, depending on the time of your call. The replacement unit will be completely refurbished, quality-tested by Panasonic technicians, and individually hand-inspected before it is shipped to you. You will keep the replacement unit and send your



original unit to us, along with a copy of your receipt.

4 This receipt *must be shipped back* with your original unit to Panasonic Company (as per instructions enclosed in your replacement unit's box).

Any unit that is replaced by Panasonic and *not* backed up by a proof of purchase by you will be subject to a minimum \$100.00 charge. Any unit that is replaced, but does not meet the terms and conditions of the limited warranty will be subject to additional charges, as per the program guidelines.

5 Once you receive your replacement unit, pack up your problem unit in the replacement unit's box. UPS will make 3 attempts within 10 days to pick-up your defective unit at no charge to you (should you be entitled to warranty service. If warranty conditions do not apply, you will be charged for all applicable shipping charges). *The product must be properly packaged in the same manner as the replacement unit, utilizing the packing materials provided.* You must make your unit available for UPS pick-up. If your unit is not available for UPS, you will be responsible for shipping unit back at your expense. Damage due to improper or inadequate packing will be charged back to your charge card as an out-of-warranty cost, as per the warranty stipulations (see back panel.)

### Requirements:

6 You must give our technicians a valid credit card number. They will keep this number on file to cover any charges that are incurred by failure to send the problem product to Panasonic Company. If your problem unit is not eligible for warranty, you will be charged for the repair of the unit and for any shipping charges associated with this program. If you do not wish to pay out-of-warranty repair costs, you will be responsible for returning the replacement unit to Panasonic and for paying all shipping charges associated with this program including the overnight delivery of replacement product to you, shipment of problem unit to Panasonic, the replacement unit back to Panasonic and the return of your original unit back to you.

#### Acceptable credit cards:

Discover VISA  
Master Card American Express (Optima)

Product that is not returned to Panasonic by 10 business days after shipment of the replacement product, will be charged to your account at Panasonic's Suggested Retail Price (see dealer for details).

Credit status will be verified prior to sending the replacement product.

Proof of Purchase must be included with the returned unit to verify warranty status.

Any parts and labor that are not covered by the limited warranty\* will be charged as a non-warranty repair and billed at Panasonic's current rate for parts and labor.

\*See back panel for one-year limited warranty.

\*\*Replacement program excludes Puerto Rico and is subject to termination at any time without advance notice.



Matsushita Consumer Electronics Company, Division of Matsushita Electric Corporation of America  
One Panasonic Way, Secaucus, New Jersey 07094

Panasonic Sales Company, Division of Matsushita Electric of Puerto Rico, Inc. ("PSC")  
Ave. 65 de Infantería, Km. 9.5  
San Gabriel Industrial Park, Carolina, Puerto Rico 00985